

# Rittal – The System.

Faster – better – everywhere.

## ► Slide rails, depth-variable, 1 U for TS IT, TE – DK 5501.460

Date : Nov 27, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Slide rails, depth-variable, 1 U for TS IT, TE – DK 5501.460

created: 27.11.2019 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

**Benefits:** Tool-free, time-saving one-man assembly from the enclosure front  
All three mounting holes in the EIA system punchings are available for screw-fastening the equipment.  
Alternatively, direct screw fastening to the 482.6 mm (19") system punchings is also possible

**Applications:** For mounting between the front and the rear pair of mounting angles  
To support heavy installed equipment  
To adapt to individual distances between 482.6 mm (19") levels

**Material:** Sheet steel

**Surface finish:** Zinc-plated

**Supply includes:** Assembly parts

**Note:** Effective contact surface 25 mm per side

## Product features

**To fit:** Enclosure type: TS IT  
Enclosure type: TE

**Installation options:** 482.6 mm (19") L mounting angles, front and rear  
482.6 mm (19") mounting frames front and rear

**Distance between levels:** min.: 400 mm  
max.: 600 mm

|                                      |   |
|--------------------------------------|---|
| <b>Contact surface:</b>              | Width: 25 mm  |
| <b>Load capacity:</b>                | 800 N   |
| <b>Packs of:</b>                     | 2 pc(s).  |
| <b>Weight/pack:</b>                  | 2.36 kg   |
| <b>Copper weight (kg per piece):</b> | 0   |
| <b>EAN:</b>                          | 4028177679016   |
| <b>Customs tariff number:</b>        | 73269098  |
| <b>ETIM 7.0:</b>                     | EC002620  |
| <b>ETIM 6.0:</b>                     | EC002620  |
| <b>eCl@ss 8.0/8.1:</b>               | 27189261  |
| <b>eCl@ss 6.0/6.1:</b>               | 27182590  |
| <b>Product description:</b>          | DK Slide rail, support surface width: 25 mm, depth-variable, 80 kg, For two 482.6 mm (19")-mounting angles (front+rear), distance between levels:: 400-600 mm |