

# Rittal – The System.

Faster – better – everywhere.

## **Optipanel – CP** **6380.020**

Date : Nov 28, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Optipanel – CP 6380.020

created: 28.11.2019 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

<b>Design:</b>	Support arm connection, rectangular 120 x 65 mm
<b>Benefits:</b>	Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems
<b>Material:</b>	Enclosure: Extruded aluminium section Corner pieces: Die-cast zinc Corner protectors: Plastic
<b>Colour:</b>	Enclosure: Natural anodised. Corner pieces: RAL 7035 Corner protectors: similar to RAL 7024
<b>Protection category IP to IEC 60 529:</b>	IP 65
<b>Supply includes:</b>	Enclosure with hinged rear panel Seals
<b>Note:</b>	The support arm connection may be swapped over by rotating the enclosure 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C Hinging of the rear panel on the longest enclosure side

## Product features

<b>For the configuration of subracks:</b>	To fit front panel width: 430 mm
<b>Installation depth:</b>	100 mm

<b>To fit front panels:</b>	with width: 430 mm with height: 343 mm
<b>Lock version:</b>	Cam
<b>Number of locks:</b>	2
<b>Lock insert:</b>	3 mm double-bit
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	5.3 kg
<b>EAN:</b>	4028177429079
<b>Customs tariff number:</b>	94032080
<b>ETIM 7.0:</b>	EC002504
<b>ETIM 6.0:</b>	EC002504
<b>eCl@ss 8.0/8.1:</b>	27180505
<b>eCl@ss 6.0/6.1:</b>	27180505
<b>Product description:</b>	CP Optipanel, for front panel BH 430x343 mm, installation depth 100 mm, Extruded aluminum section, Support arm connection 120x65 mm
<b>Approvals</b>	
<b>Approvals:</b>	UL + C-UL
<b>Certificates:</b>	Protection category
<b>Declarations:</b>	Declaration of conformity