

Rittal – The System.

Faster – better – everywhere.

Optipanel – CP **6380.410**

Date : Feb 18, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Optipanel – CP 6380.410

created: 18.02.2019 build on www.rittal.com/uk-en



Product description

Design:	Support arm connection Ø 130 mm
Benefits:	Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems
Material:	Enclosure: Extruded aluminium section Corner pieces: Die-cast zinc Corner protectors: Plastic
Colour:	Enclosure: Natural anodised. Corner pieces: RAL 7035 Corner protectors: similar to RAL 7024
Protection category IP to IEC 60 529:	IP 65
Supply includes:	Enclosure with hinged rear panel Seals Seals and assembly parts for front panels
Note:	The support arm connection may be swapped over by rotating the enclosure 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C Hinging of the rear panel on the longest enclosure side

Product features

For the configuration of subracks:	To fit front panel width: 520 mm
Installation depth:	150 mm

To fit front panels:	with width: 520 mm with height: 400 mm
Lock version:	Cam
Number of locks:	2
Lock insert:	3 mm double-bit
Packs of:	1 pc(s).
Weight/pack:	7.3 kg
EAN:	4028177663169
Customs tariff number:	94032080
ETIM 6.0:	EC002504
ETIM 5.0:	EC002504
eCl@ss 8.0/8.1:	27180505
eCl@ss 7.0/7.1:	27180505
eCl@ss 6.0/6.1:	27180505
eCl@ss 5.1/5.1.4:	27180505
Product description:	CP Optipanel, for front panel BH 520x400 mm, installation depth 150 mm, Extruded aluminum section, Support arm connection Ø 130 mm
Approvals	
Approvals:	UL + C-UL
Declarations:	Declaration of conformity