Rittal – The System.

Faster – better – everywhere.





ENCLOSURES

POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Optipanel – CP 6380.510 created: 20.02.2019 build on www.rittal.com/uk-en



Product description	
Design:	Support arm connection Ø 130 mm
Benefits:	Aluminium enclosure, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems
Material:	Enclosure: Extruded aluminium section Corner pieces: Die-cast zinc Corner protectors: Plastic
Colour:	Enclosure: Natural anodised. Corner pieces: RAL 7035 Corner protectors: similar to RAL 7024
Protection category IP to IEC 60 529:	IP 65
Supply includes:	Enclosure with hinged rear panel Seals Seals and assembly parts for front panels
Note:	The support arm connection may be swapped over by rotating the enclosure 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C Hinging of the rear panel on the longest enclosure side
Product features	
For the configuration of subracks:	To fit front panel width: 520 mm
Installation depth:	150 mm

To fit front panels:	with width: 520 mm with height: 500 mm
Lock version:	Cam
Number of locks:	2
Lock insert:	3 mm double-bit
Packs of:	1 pc(s).
Weight/pack:	8.3 kg
EAN:	4028177663183
Customs tariff number:	94032080
ETIM 6.0:	EC002504
ETIM 5.0:	EC002504
eCl@ss 8.0/8.1:	27180505
eCl@ss 7.0/7.1:	27180505
eCl@ss 6.0/6.1:	27180505
eCl@ss 5.1/5.1.4:	27180505
Product description:	CP Optipanel, for front panel BH 520x500 mm, installation depth 150 mm, Extruded aluminum section, Support arm connection $Ø$ 130 mm
Approvals	
Approvals:	UL + C-UL
Declarations:	Declaration of conformity