

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted enclosures EL, 3-part with punched rails and mounting angles, depth-variable – DK 7715.135

Date : Jul 28, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted enclosures EL, 3-part with punched rails and mounting angles, depth-variable – DK 7715.135

created: 28.07.2017 build on www.rittal.com/uk-en



Product description

Design: with punched rails and mounting angles, depth-variable

Description: Wall-mounted enclosure with optimum accessibility due to hinged part.

Material: Wall and hinged part: Sheet steel, 1.5 mm
Viewing window: Single-pane safety glass, 3 mm

Surface finish: Powder-coated

Colour: Wall and hinged part: RAL 7035
Glazed door: RAL 7035/7015 (slate grey)

**Protection category
IP to IEC 60 529:** IP 55

Supply includes: Wall section with solid gland plate, top and bottom, two vertical mounting rails and C rail, horizontal, for cable clamping
Hinged part with 25 mm pitch pattern of holes in the front and rear frame, and two 482.6 mm (19") mounting angles at the front, infinitely depth-variable
4 wall mounting brackets 10 mm
Designer glazed door
1 Mini-comfort handle
1 Security lock 3524 E

Basic material: Sheet steel

Product features

Dimensions: Width: 600 mm

Height: 746 mm
Units: 15 U
Depth: 473 mm

Depth hinged part:	316 mm
Installation depth:	420 mm
Clearances:	Clearance width: 502 mm Clearance height: 683 mm
Wall section:	Depth: 135 mm
Load capacity:	Hinged part, static (max.): 750 N
Packs of:	1 pc(s).
Weight/pack:	41 kg
EAN:	4028177324206
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC002500
eCl@ss 8.0/8.1:	27142408
eCl@ss 7.0/7.1:	27180208
eCl@ss 6.0/6.1:	27180208
eCl@ss 5.1/5.1.4:	27180204
Product description (long):	DK Wall-mounted enclosures, 3-part, WHD: 600x746x473 mm, 15 U, With punched rails, and mounting angles, depth-variable
Approvals	
Approvals:	UL + C-UL