Rittal - The System.

Faster – better – everywhere.

OM supports without contact system – SV 9340.270

Date: Jan 14, 2019



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

OM supports without contact system — SV 9340.270 created: 14.01.2019 build on www.rittal.com/uk-en



Product description	1
Description:	For mounting of switchgear with external power supply.
Material:	Polyamide (PA 6.6) Fire protection corresponding to UL 94-V0
Colour:	Chassis: RAL 7035
Product features	
To fit busbars:	with cross-section height: 5 mm with cross-section height: 10 mm
Number of poles:	3-pole
For bar systems with centre-to-centre spacing:	60 mm
Dimensions:	Width: 55 mm Height: 272 mm
Support frame:	Width: 55 mm Height: 237 mm
Number of support rails:	1
Height of support rails:	10 mm
Support rail type:	TS 55D-V

© Rittal 2019

Support frame support:	yes
Packs of:	1 pc(s).
Weight/pack:	0.26 kg
EAN:	4028177502475
Customs tariff number:	39269097
ETIM 6.0:	EC001166
ETIM 5.0:	EC001166
eCl@ss 8.0/8.1:	27400607
eCl@ss 7.0/7.1:	27400607
eCl@ss 6.0/6.1:	27400607
eCl@ss 5.1/5.1.4:	27370302
Product description:	SV OM Support, WH: 55x272 mm, support frame, support rail TS 55D-V, without contact system
Approvals	
Approvals:	ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2019