

Rittal – The System.

Faster – better – everywhere.

OM adaptors with connection cables – SV 9340.350

Date : Jan 16, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



OM adaptors with connection cables – SV 9340.350

created: 16.01.2017 build on www.rittal.com/uk-en



Product description

Material: Polyamide (PA 6.6)
Fire protection corresponding to UL 94-V0

Colour: Chassis: RAL 7035

Note: The technical data may vary for UL applications

Product features

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 45 mm
Height: 208 mm

Rated operating voltage: 690 V, 3~

Connection cable: Cross-section: AWG 10
Length: 130 mm

Support frame: Width: 45 mm
Height: 170 mm

Rated current (max.):	32 A
Number of support rails:	1
Height of support rails:	10 mm
Support rail type:	TS 45C
Packs of:	1 pc(s).
Weight/pack:	0.3 kg
EAN:	4028177525559
Customs tariff number:	85369095
ETIM 6.0:	EC001531
ETIM 5.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 7.0/7.1:	27370304
eCl@ss 6.0/6.1:	27370304
eCl@ss 5.1/5.1.4:	27370302

Approvals

Approvals: ABS
C-UL
DNV GL
Germanischer Lloyd
UL + C-UL

Declarations: Declaration of conformity