

Rittal – The System.

Faster – better – everywhere.

OM adaptors with connection cables – SV 9340.780

Date : Jun 30, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



OM adaptors with connection cables – SV 9340.780

created: 30.06.2021 build on www.rittal.com/uk-en



Product description

Material:	Polyamide Fire protection corresponding to UL 94-V0
Colour:	Chassis: RAL 7035
Note:	The technical data may vary for UL applications

Product description

To fit busbars:	with cross-section height: 5 mm with cross-section height: 10 mm
Number of poles:	3-pole
For bar systems with centre-to-centre spacing:	60 mm
Dimensions:	Width: 45 mm Height: 208 mm
Rated current max.:	16 A
Rated operating voltage:	690 V, 3~
Connection cable:	Cross-section: AWG 12 Length: 165 mm
Support frame:	Width: 45 mm Height: 170 mm

Number of support rails:	2
Height of support rails:	10 mm
Support rail type:	TS 45D TS 45D-V
Packs of:	1 pc(s).
Weight/pack:	0.3 kg
Copper weight (kg per piece):	0.04
EAN:	4028177701410
Customs tariff number:	85369095
ETIM 7.0:	EC001531
ETIM 6.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 6.0/6.1:	27370304
Product description:	SV OM adaptor, 16 A, 690 V, 3-pole, connection cable AWG 12, WH: 45x208 mm, support frame, support rail TS 45D, TS 45D-V
Approvals	
Approvals:	ABS Lloyds Register of Shipping
Certificates:	EAC
Declarations:	Declaration of conformity