

Rittal – The System.

Faster – better – everywhere.

► Ex enclosures Stainless steel, empty enclosure with hinged door – KE 9403.600

Date : Jan 16, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Ex enclosures Stainless steel, empty enclosure with hinged door – KE 9403.600

created: 16.01.2019 build on www.rittal.com/uk-en



Product description

Applications:	Zone 1 and 2 or 21 and 22 to 94/9/EC Ambient temperature range: -30 °C...+80 °C The specified temperatures may be limited by the installed equipment Protection type to EN 60 079: Equipment protection due to increased safety, equipment protection due to enclosure
Material:	Enclosure: Stainless steel 1.4301 (AISI 304) Door: Stainless steel 1.4301 (AISI 304), all-round foamed-in silicone seal Mounting plate: Sheet steel
Surface finish:	Enclosure: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Certificates:	IEC Ex PTB 09.0035U: yes PTB 02 ATEX 1082U: yes
Supply includes:	Enclosure Door Mounting plate
Basic material:	Stainless steel

Product features

Dimensions: Width: 380 mm

Height: 380 mm
Depth: 210 mm

Mounting plate:	Width: 334 mm Height: 355 mm
Number of cam locks:	1
Lock version:	Cam
Number of locks:	1
Lock insert:	3 mm double-bit
Weight/pack:	10.1 kg
ETIM 5.0:	EC002503
eCl@ss 8.0/8.1:	27180502
eCl@ss 6.0/6.1:	27180502
Product description:	KEL Ex enclosure, WHD: 380x380x210 mm, Stainless steel 1.4301, with mounting plate, Empty enclosure with hinged door
Approvals	
Approvals:	ATEX IEC Ex UL + C-UL
Certificates:	EAC Ex
Declarations:	Manufacturer's declaration