

Rittal – The System.

Faster – better – everywhere.

► Polycarbonate enclosures PK without knockouts – PK 9504.000

Date : Aug 2, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Polycarbonate enclosures PK without knockouts – PK 9504.000

created: 02.08.2017 build on www.rittal.com/uk-en



Product description

| | |
|--|--|
| Applications: | Ambient temperature range: -35°C...+80°C The specified temperatures may be limited by the installed equipment |
| Material: | Housing: Fibre-glass reinforced polycarbonate Cover grey: Fibreglass-reinforced polycarbonate, all-round foamed-in PU seal Cover screws: Polyamide Insulating bungs: Polyethylene |
| Colour: | RAL 7035 |
| Protection category IP to IEC 60 529: | IP 66 |
| Protection category NEMA: | NEMA 4X |
| Supply includes: | Enclosure with cover Cover screws Insulating bungs for wall mounting screws |
| Basic material: | Polycarbonate |

Product features

| | |
|--------------------|---|
| Dimensions: | Width: 94 mm Height: 94 mm Depth: 57 mm |
| Cover: | grey |

| | |
|------------------------------------|---|
| Ambient temperature range: | -35°C...+80°C |
| Packs of: | 6 pc(s). |
| Weight/pack: | 1.07 kg |
| EAN: | 4028177139091 |
| Customs tariff number: | 94037000 |
| ETIM 6.0: | EC000261 |
| ETIM 5.0: | EC002600 |
| eCl@ss 8.0/8.1: | 27180101 |
| eCl@ss 7.0/7.1: | 27180101 |
| eCl@ss 6.0/6.1: | 27180101 |
| eCl@ss 5.1/5.1.4: | 27180102 |
| Product description (long): | PK Polycarbonate enclosure, WHD: 94x94x57 mm, fibreglass-reinforced polycarbonate, without knockouts, with grey cover |
| Approvals | |
| Approvals: | Bureau Veritas C-UL UL |
| Declarations: | Declaration of conformity |