

# Rittal – The System.

Faster – better – everywhere.

## ► Polycarbonate enclosures PK without knockouts – PK 9507.000

Date : Aug 2, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Polycarbonate enclosures PK without knockouts – PK 9507.000

created: 02.08.2017 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

<b>Applications:</b>	Ambient temperature range: -35°C...+80°C The specified temperatures may be limited by the installed equipment
<b>Material:</b>	Housing: Fibre-glass reinforced polycarbonate Cover grey: Fibreglass-reinforced polycarbonate, all-round foamed-in PU seal Cover screws: Polyamide Insulating bungs: Polyethylene
<b>Colour:</b>	RAL 7035
<b>Protection category IP to IEC 60 529:</b>	IP 66
<b>Protection category NEMA:</b>	NEMA 4X
<b>Supply includes:</b>	Enclosure with cover Cover screws Insulating bungs for wall mounting screws
<b>Basic material:</b>	Polycarbonate

## Product features

<b>Dimensions:</b>	Width: 110 mm Height: 110 mm Depth: 90 mm
<b>Cover:</b>	grey

<b>Ambient temperature range:</b>	-35°C...+80°C
<b>Packs of:</b>	6 pc(s).
<b>Weight/pack:</b>	1.82 kg
<b>EAN:</b>	4028177139213
<b>Customs tariff number:</b>	94037000
<b>ETIM 6.0:</b>	EC000261
<b>ETIM 5.0:</b>	EC002600
<b>eCl@ss 8.0/8.1:</b>	27180101
<b>eCl@ss 7.0/7.1:</b>	27180101
<b>eCl@ss 6.0/6.1:</b>	27180101
<b>eCl@ss 5.1/5.1.4:</b>	27180102
<b>Product description (long):</b>	PK Polycarbonate enclosure, WHD: 110x110x90 mm, fibreglass-reinforced polycarbonate, without knockouts, with grey cover
<b>Approvals</b>	
<b>Approvals:</b>	Bureau Veritas C-UL UL
<b>Declarations:</b>	Declaration of conformity