

Rittal – The System.

Faster – better – everywhere.

► Polycarbonate enclosures PK without knockouts – PK 9510.000

Date : Aug 2, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Polycarbonate enclosures PK without knockouts – PK 9510.000

created: 02.08.2017 build on www.rittal.com/uk-en



Product description

Applications:	Ambient temperature range: -35°C...+80°C The specified temperatures may be limited by the installed equipment
Material:	Housing: Fibre-glass reinforced polycarbonate Cover grey: Fibreglass-reinforced polycarbonate, all-round foamed-in PU seal Cover screws: Polyamide Insulating bungs: Polyethylene
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4X
Supply includes:	Enclosure with cover Cover screws Insulating bungs for wall mounting screws
Basic material:	Polycarbonate

Product features

Dimensions:	Width: 130 mm Height: 130 mm Depth: 75 mm
Cover:	grey

Ambient temperature range:	-35°C...+80°C
Packs of:	4 pc(s).
Weight/pack:	1.33 kg
EAN:	4028177139336
Customs tariff number:	94037000
ETIM 6.0:	EC000261
ETIM 5.0:	EC002600
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	PK Polycarbonate enclosure, WHD: 130x130x75 mm, fibreglass-reinforced polycarbonate, without knockouts, with grey cover
Approvals	
Approvals:	Bureau Veritas C-UL UL
Declarations:	Declaration of conformity