

Rittal – The System.

Faster – better – everywhere.

Mini-PLS busbar connection adaptor – SV 9613.000

Date : Jan 16, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Mini-PLS busbar connection adaptor – SV 9613.000

created: 16.01.2019 build on www.rittal.com/uk-en



Product description

Material: Polyamide (PA 6.6)
Fire protection corresponding to UL 94-V0

Colour: RAL 7035
Chassis: RAL 9011

Product features

Number of poles: 3-pole

Dimensions: Width: 54 mm
Height: 160 mm

Clamping area for laminated copper bars: Width: 10 mm
Height: 8 mm

Connection for round conductor cross-sections: 1,5 mm² - 35 mm²
Note: Wire end ferrules should be used with fine wire conductors.

Rated current (max.): 63 A

Cable outlet: Top/bottom

Weight/pack: 0.45 kg

ETIM 5.0: EC001531

eCl@ss 6.0/6.1: 27400613

Product description: SV Mini-PLS busbar connection adaptor, 63 A, 690 V, 3-pole, round conductor connection 1,5-35 mm², clamping area WH: 10x8 mm

Approvals

Certificates: EAC

Declarations: Declaration of conformity