

Rittal – The System.

Faster – better – everywhere.

CS New Basic enclosures – CS 9784.540

Date : Aug 21, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CS New Basic enclosures – CS 9784.540

created: 21.08.2017 build on www.rittal.com/uk-en



Product description

Description: Outdoor enclosure with 100 mm transport plinth and rain canopy with projections on all sides.

Material: Aluminium AlMg3

Surface finish: Powder-coated
UV-resistant pure polyester

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 55

**Protection category
NEMA:** NEMA 3R

IK Code: IK07

Supply includes: Single-walled outdoor enclosure, fully preconfigured
Basic enclosure with gland plate, three-part
25 mm system punchings in the roof, base, front and in the enclosure depth
Front door(s) with door stay, swing lever handle and semi-cylinder, lock BJ 20027
Transport plinth with screw-fastened trim panels front and rear
Rain canopy

Basic material: Aluminium

Product features

Dimensions: Width: 1200 mm
Height: 1200 mm
Height (base/plinth): 100 mm

Height (mounted): 1355 mm
Depth: 500 mm

Clearances:	Clearance width: 512 mm Clearance height: 1112 mm Clearance depth: 449 mm
Rain canopy:	Width: 1250 mm Height: 55 mm Depth: 550 mm
Number of doors:	2
Centre bar:	With removable centre bar, 2 lockable doors
Packs of:	1 pc(s).
Weight/pack:	66 kg
EAN:	4028177569218
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC002499
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180302
Product description (long):	CS New Basic enclosure, WHD: 1200x1200x500 mm, aluminum, with 100 mm transport plinth and rain canopy, two doors at the front
Approvals	
Declarations:	Declaration of conformity