Rittal - The System.

Faster – better – everywhere.

Bus enclosures BG Stainless steel – BG 1558.010

Date : Jul 26, 2017



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Bus enclosures BG Stainless steel - BG 1558.010

created: 26.07.2017 build on www.rittal.com/uk-en



D 1 1		
Product	des	crintion
1 IOGGC	aco	01160011

Material: Enclosure: Stainless steel 1.4301 (AISI 304)

Cover: Stainless steel 1.4301 (AISI 304), all-round foamed-in PU seal

180° hinges: Die-cast zinc

Surface finish: Enclosure and cover: Brushed, grain 240

180° hinges: chrome-plated

Protection category IP to IEC 60 529:

IP 66

Protection category

NEMA:

NEMA 4X

Supply includes:

Enclosure with cover 180° hinges (2) Support rail TS 35/7.5

Quick-release fastener including plastic bushes

Basic material:

Stainless steel

Product features

Dimensions: Width: 400 mm Height: 200 mm

Depth: 123 mm

Support rails: Qty. (type TS 35/7.5): 1

Design support rail: adjustable on profile strip

Material thickness: Enclosure: 1.5 mm

© Rittal 2017

Door hinge:	bottom
Lock version:	Quick-release fastener including plastic bushes
Number of locks:	2
Packs of:	1 pc(s).
Weight/pack:	4.5 kg
EAN:	4028177009912
Customs tariff number:	94032080
ETIM 6.0:	EC002713
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
e Cl@ss 7.0/7.1:	27180101
e Cl@ss 6.0/6.1:	27180101
e CI@ss 5.1/5.1.4:	27180103
Product description (long):	BG Bus enclosure, WHD: 400x200x123 mm, Stainless steel 1.4301, without mounting plate, with cover, with support rail
Approvals	
Approvals:	Lloyds Register of Shipping NA TÜV UL + C-UL
Certificates:	EAC Protection category
Declarations:	Declaration of conformity

2017 © Rittal Ltd UK

© Rittal 2017 2