

Rittal – The System.

Faster – better – everywhere.

Security lock – SZ 2418.000

Date : Jan 18, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Security lock – SZ 2418.000

created: 18.01.2019 build on www.rittal.com/uk-en



Product description

Description:	Fitted to doors, to protect against contact with live electrical equipment whilst the master switch is ON.
Function principle:	Locks the door when the master switch is ON. Mains power (voltage) is only enabled whilst the door is closed. Monitoring of the lock magnet via an additional closing contact.
Supply includes:	Lock Actuator Angle bracket Assembly parts

Product features

Rated operating voltage:	24 V (DC)
Power consumption:	With DC: 8 W
Rated insulation voltage:	400 V AC
Rated impulse withstand voltage, phase to phase:	4000 V AC
Weight/pack:	0.74 kg
ETIM 5.0:	EC002626
eCl@ss 8.0/8.1:	27189266

Product description:	SZ Security lock, 24 V DC
-----------------------------	---------------------------

Approvals

Approvals:	CSA UL
-------------------	-----------

Certificates:	EAC
----------------------	-----

Declarations:	Declaration of conformity
----------------------	---------------------------
