Rittal – The System.

Faster – better – everywhere.

Interface flaps, modular – SZ 2482.590

Date : Jan 22, 2019



ENCLOSURES

POWER DISTRIBUTION >> CLIMATE CONTROL

) IT INFRASTRUCTURE > Software & Services

FRIEDHELM LOH GROUP

Interface flaps, modular – SZ 2482.590 created: 22.01.2019 build on www.rittal.com/uk-en



Product description	n
Description:	For universal use in all situations where rapid access to interfaces and sockets is needed. The affected enclosure remains closed and is therefore protected from ambient influences and unauthorised access.
Function principle:	The mounting frame has a flap which snaps into position in various stages at opening angles of 90 to 180°. A snap fastener ensures reliable sealing. This may be locked if required. All SUB-D interfaces may be rotated while in use
Material:	Mounting frame and metal flap: Fine die-cast zinc Plastic flap: Polycarbonate (semi-transparent) Lock: Polycarbonate
Surface finish:	Mounting frame and metal flap: Matt nickel-plated
Colour:	Lock: RAL 7024 Screw terminals: yellow (RAL 1016)
Protection category IP to IEC 60 529:	IP 65 with sealed flap and proper assembly
Product features	
Installation options:	As programming interface for controllers As maintenance access for networks For temporary connection of additional equipment For quick connection to existing network structures For programming and maintenance of integral components
Packs of:	1 pc(s).
Weight/pack:	0.04 kg

1

EAN:	4028177490888
Customs tariff number:	85369095
ETIM 6.0:	EC002625
ETIM 5.0:	EC002608
e Cl@ss 8.0/8.1:	27189234
e Cl@ss 7.0/7.1:	27189234
eCl@ss 6.0/6.1:	27189234
eCl@ss 5.1/5.1.4:	27189238
Product description:	SZ Interface flap, modular, interface inserts, Blanking plate, slimline
Approvals	
Approvals:	C-UR UR + C-UR
Certificates:	EAC