

Rittal – The System.

Faster – better – everywhere.

LED system light – SZ 2500.200

Date : Dec 6, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



LED system light – SZ 2500.200

created: 06.12.2016 build on www.rittal.com/uk-en



Product description

Benefits: Optimum illumination of the entire enclosure
Optionally with clip, screw and magnetic attachment
A configuration to suit every application

Equipment: 90° rotating connector
Adjustable light distribution

Material: Light body: Extruded aluminium
Light cover: Polycarbonate (halogen-free)
Light ends: PC-ABS (halogen-free)

Colour: Enclosure: RAL 7016

Supply includes: Assembly screws

Product features

Dimensions: Width: 437 mm
Height: 75 mm
Depth: 23 mm

Rated operating voltage: 100 V - 240 V, 1~, 50 Hz/60 Hz

Installation options: Screw-fasten or clip directly onto the TS/SE section
AE, CM, TP: with universal bracket
AE: with rail for interior installation
TE 8000: With mounting kit magnet

Operating temperature: Operation (environment): -20°C...+55°C

Power consumption:	11 W
Rated insulation voltage:	300 V AC
Rated impulse withstand voltage, phase to earth:	2500 V AC
Luminous flux:	900 lm
Light colour:	4000 K (neutral white)
Protection category:	II (all-insulated)
Overvoltage category:	II
Connection options:	Infeed, 3-pole Through-wiring, 3-pole Door-operated switch
Light – installation type:	Screw-fastening Clip attachment Magnetic attachment (accessory)
Packs of:	1 pc(s).
Weight/pack:	0.57 kg
EAN:	4028177806955
Customs tariff number:	94054099
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
eCl@ss 5.1/5.1.4:	27189241

Approvals

Approvals: ENEC
UL + C-UL

Certificates:	EAC
Declarations:	Declaration of conformity