## Rittal - The System.

Faster – better – everywhere.

## LED system light – SZ 2500.200

Date: Dec 6, 2016



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## LED system light – SZ 2500.200

created: 06.12.2016 build on www.rittal.com/uk-en



Draduct	description	١
riouuci	uescription	ı

Benefits: Optimum illumination of the entire enclosure

Optionally with clip, screw and magnetic attachment

A configuration to suit every application

90° rotating connector **Equipment:** 

Adjustable light distribution

Material: Light body: Extruded aluminium

Light cover: Polycarbonate (halogen-free)

Light ends: PC-ABS (halogen-free)

Colour: Enclosure: RAL 7016

Supply includes: Assembly screws

## **Product features**

Width: 437 mm **Dimensions:** 

> Height: 75 mm Depth: 23 mm

Rated operating

voltage:

100 V - 240 V, 1~, 50 Hz/60 Hz

Screw-fasten or clip directly onto the TS/SE section Installation options:

> AE, CM, TP: with universal bracket AE: with rail for interior installation TE 8000: With mounting kit magnet

Operating temperature: Operation (environment): -20°C...+55°C

© Rittal 2016 1

Power consumption:	11 W
Rated insulation voltage:	300 V AC
Rated impulse withstand voltage, phase to earth:	2500 V AC
Luminous flux:	900 lm
Light colour:	4000 K (neutral white)
Protection category:	II (all-insulated)
Overvoltage category:	II
Connection options:	Infeed, 3-pole Through-wiring, 3-pole Door-operated switch
Light – installation type:	Screw-fastening Clip attachment Magnetic attachment (accessory)
Packs of:	1 pc(s).
Weight/pack:	0.57 kg
EAN:	4028177806955
Customs tariff number:	94054099
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCI@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
e CI@ss 5.1/5.1.4:	27189241
Approvals	
Approvals:	ENEC UL + C-UL

© Rittal 2016

Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2016 3