Rittal - The System.

Faster – better – everywhere.

LED system light – SZ 2500.211

Date: Nov 25, 2019



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

LED system light – SZ 2500.211 created: 25.11.2019 build on www.rittal.com/uk-en



Product description		
Design:	with socket	
Benefits:	Optimum illumination of the entire enclosure Optionally with clip, screw and magnetic attachment A configuration to suit every application	
Equipment:	Socket 90° rotating connector Adjustable light distribution	
Material:	Light body: Extruded aluminium Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS (halogen-free)	
Colour:	Enclosure: RAL 7016	
Protection category IP to IEC 60 529:	IP 20	
Supply includes:	Assembly screws	
Product features		
Dimensions:	Width: 437 mm Height: 80 mm Depth: 44 mm	
Rated operating voltage:	100 V - 240 V, 1~, 50 Hz/60 Hz	
Installation options:	Directly onto the enclosure section with 25 mm pitch pattern	

© Rittal 2019

Operating temperature:	Operation (environment): -20 °C+55 °C
Power consumption:	11 W
Equipment (electrical):	Jack/socket (type): GB (type G, BS 1363)
Rated insulation voltage:	300 V AC
Rated impulse withstand voltage, phase to earth:	2500 V AC
Luminous flux:	900 lm
Light colour:	4000 K (neutral white)
Protection class:	II (all-insulated)
Overvoltage category:	II
Connection options:	Infeed, 3-pole Through-wiring, 3-pole Door-operated switch
Light – installation type:	Screw-fastening Clip attachment
Packs of:	1 pc(s).
Weight/pack:	0.61 kg
Copper weight (kg per piece):	0
EAN:	4028177811355
Customs tariff number:	94054099
ETIM 7.0:	EC000321
ETIM 6.0:	EC000321
e CI@ss 8.0/8.1:	27189241
e CI@ss 6.0/6.1:	27189241
Product description:	SZ System Light LED, 900 Lumen, L: 437 mm, 100-240 V, with eaerthing-pin socket for Great Britain

© Rittal 2019

Approvals	
Approvals:	ENEC
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2019 3