Rittal - The System.

Faster – better – everywhere.

LED system light – SZ 2500.300

Date: Jan 15, 2019



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

LED system light – SZ 2500.300 created: 15.01.2019 build on www.rittal.com/uk-en



Dimensions:

Product descriptio	n
Description:	LED system light – the first light especially for enclosures! Highly innovative LED technology for even more light into the very last corner.
Benefits:	Optimum illumination of the entire enclosure Optionally with clip, screw and magnetic attachment A configuration to suit every application
Equipment:	Motion sensor 90° rotating connector Adjustable light direction Adjustable light distribution
Motion sensor:	yes
Material:	Light body: Extruded aluminium Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS (halogen-free)
Colour:	Enclosure: RAL 7016
Protection category IP to IEC 60 529:	IP 20
Supply includes:	Assembly screws
Product features	

© Rittal 2019

1

Width: 437 mm Height: 85 mm Depth: 37 mm

Installation options: Screw-fasten or clip directly onto the TS/SE section AE, CM, TP, with universal bracket AE, With rail for intender installation with real for intender installation. Operating temperature: Operation (environment): -20°C+55°C Power consumption: 13 W Rated insulation voltage; phase to earth: 2500 V AC Light colour: 4000 K (neutral white) Protection category: II (all-insulated) Connection options: Infeed, 3-pole Through-wring, 3-pole Light – installation type: Screw-fastening type: Magnetic attachment (accessory) Packs of: 1 pc(s). Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff number: EC000321 ETIM 5.0: EC000321 eCl@es 8.0/8.1: 27189241 eCl@es 8.0/6.1: 27189241	Rated operating voltage:	100 V - 240 V, 1~, 50 Hz/60 Hz
temperature: 13 W Rated insulation voltage: 300 V AC Rated impulse withstand voltage, phase to earth: 2500 V AC Luminous flux: 1200 lm Light colour: 4000 K (neutral white) Protection category: II (all-insulated) Overvoltage category: II Connection options: Infeed, 3-pole Through-wiring, 3-pole Light – installation type: Screw-fastening Clip attachment (accessory) Packs of: 1 pc(s). Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff number: 94054099 ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241	Installation options:	AE, CM, TP: with universal bracket
Rated insulation voltage: 300 V AC Rated impulse withstand voltage, phase to earth: 2500 V AC Luminous flux: 1200 lm Light colour: 4000 K (neutral white) Protection category: II (all-insulated) Overvoltage category: II Light – installation type: Screw-fastening Clip attachment (accessory) Packs of: 1 pc(s). Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff number: 94054099 ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241		Operation (environment): -20°C+55°C
voltage: Rated impulse withstand voltage, phase to earth: 2500 V AC withstand voltage, phase to earth: Luminous flux: 1200 lm Light colour: 4000 K (neutral white) Protection category: II (all-insulated) Connection options: Infeed, 3-pole Through-wiring, 3-pole Light – installation type: Screw-fastening Clip attachment (accessory) Packs of: 1 pc(s). Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff umber: 94054099 ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 ecl@ss 7.0/7.1: 27189241	Power consumption:	13 W
withstand voltage, phase to earth: Luminous flux: 1200 lm Light colour: 4000 K (neutral white) Protection category: II (all-insulated) Overvoltage category: II Connection options: Infeed, 3-pole Through-wiring, 3-pole Light – installation type: Clip attachment (accessory) Packs of: 1 pc(s). Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff number: EC000321 ETIM 6.0: EC000321 ECI@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241		300 V AC
Light colour: 4000 K (neutral white) Protection category: II (all-insulated) Connection options: Infeed, 3-pole Through-wiring, 3-pole Light – installation type: Clip attachment (accessory) Packs of: 1 pc(s). Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff number: ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241	withstand voltage,	2500 V AC
Protection category: II (all-insulated) Overvoltage category: II Connection options: Infeed, 3-pole Through-wiring, 3-pole Light – installation type: Screw-fastening Clip attachment (accessory) Packs of: 1 pc(s). Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff number: 94054099 ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCI@ss 8.0/8.1: 27189241 eCI@ss 7.0/7.1: 27189241	Luminous flux:	1200 lm
Overvoltage category: II Connection options: Infeed, 3-pole Through-wiring, 3-pole Light – installation type: Screw-fastening Clip attachment (accessory) Packs of: 1 pc(s). Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff number: 94054099 ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241	Light colour:	4000 K (neutral white)
Connection options: Infeed, 3-pole Through-wiring, 3-pole Light – installation type: Screw-fastening Clip attachment (accessory) Packs of: 1 pc(s). Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff number: 94054099 ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCI@ss 8.0/8.1: 27189241 eCI@ss 7.0/7.1: 27189241	Protection category:	II (all-insulated)
Through-wiring, 3-pole	Overvoltage category:	II
type: Clip attachment Magnetic attachment (accessory) Packs of: 1 pc(s). Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff number: 94054099 ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241	Connection options:	
Weight/pack: 0.65 kg EAN: 4028177809864 Customs tariff number: 94054099 ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241	•	Clip attachment
EAN: 4028177809864 Customs tariff number: 94054099 ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241	Packs of:	1 pc(s).
Customs tariff number: 94054099 ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241	Weight/pack:	0.65 kg
number: ETIM 6.0: EC000321 ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241	EAN:	4028177809864
ETIM 5.0: EC000321 eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241		94054099
eCl@ss 8.0/8.1: 27189241 eCl@ss 7.0/7.1: 27189241	ETIM 6.0:	EC000321
eCl@ss 7.0/7.1: 27189241	ETIM 5.0:	EC000321
	eCl@ss 8.0/8.1:	27189241
eCl@ss 6.0/6.1: 27189241	eCl@ss 7.0/7.1:	27189241
	eCl@ss 6.0/6.1:	27189241

© Rittal 2019

eCl@ss 5.1/5.1.4:	27189241
Product description:	SZ System Light LED, 1200 Lumen, L: 437 mm, 100-240 V, with integral motion detector
Approvals	
Approvals:	CCC CSA ENEC UL + C-UL
Certificates:	EAC

Declaration of conformity

Declarations:

© Rittal 2019 3