Rittal – The System.

Faster – better – everywhere.

System windows for TS, SE – FT 2735.510



ENCLOSURES

POWER DISTRIBUTION >> CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

System windows for VX, TS, SE – FT 2735.510 created: 24.01.2019 build on www.rittal.com/uk-en



Product description

Description:	To conceal display and operating instruments or cut-outs, and to protect against dirt and liquids as well as unauthorised access.
Benefits:	 Base frame: Easily screw-fastened to the door thanks to modified dimensions (tubular door frame may be used as a drilling template). Base frame: Readily height-adjustable. Base frame: Stabilises the door cut-out. Base frame: Conceals the cut edge. Base frame: There is no dirt on the seal, the glass is protected from being lifted out, dir cannot drop inside, and moisture cannot run behind the window when opening. Base frame: Frame section height 30 mm or 60 mm Viewing window: Made from single-pane safety glass: High level of resistance to solvents and scratches, anti-static, reduced risk of injury if broken. Viewing window: Hinge with 180° opening angle, easily inserted.
Material:	Extruded aluminium section with die-cast zinc corner pieces and single-pane safety glass.
Surface finish:	Base frame: Powder-coated on the outside in RAL 7035 Hinge and lock section: Natural-anodised
Protection category IP to IEC 60 529:	IP 54
Note:	Standard double-bit lock insert may be exchanged for lock inserts 27 mm, type A, and/or for lock system Ergoform-S (except H = 270 mm).
Product features	
To fit:	Enclosure type: VX Enclosure type: TS Enclosure type: SE Width: = 600 mm

Dimensions:	Width: 500mm Height: 370mm Depth: 47mm
Viewing area:	Width: 363 mm Height: 298 mm
Build depth for components (max.):	33 mm
Packs of:	1 pc(s).
Weight/pack:	4.8 kg
EAN:	4028177476295
Customs tariff number:	76101000
ETIM 6.0:	EC002527
ETIM 5.0:	EC002527
e Cl@ss 8.0/8.1:	27182301
eCl@ss 7.0/7.1:	27182301
eCl@ss 6.0/6.1:	27182301
e Cl@ss 5.1/5.1.4:	27182301
Product description:	FT System window, for TS, SE, 30 section, WHD: 500x370x47 mm, for W: 600 mm
Approvals	
Certificates:	EAC
Declarations:	Manufacturer's declaration