

# Rittal – The System.

Faster – better – everywhere.

## Enclosure heater without fan – SK 3105.330

Date : May 3, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Enclosure heater without fan – SK 3105.330

created: 03.05.2019 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

**Supply includes:** PTC heater  
Quick-connection terminal  
Assembly parts

**Note:** For precise temperature control inside the enclosure, we recommend the enclosure internal thermostat or the digital enclosure internal temperature display and thermostat. In order to prevent condensation on assemblies, a hygostat is recommended to regulate heating. In larger enclosures, even heat distribution is best achieved by installing several low-output heaters. The installation of heaters is generally advisable, in order to prevent condensation.

**Note on Model No.:** Special voltages available on request. We reserve the right to make technical modifications.

## Product features

**Continuous thermal output at 10 °C:** 23 W - 30 W

**Rated operating voltage:** 110 V - 240 V, 1~, 50 Hz/60 Hz

**Dimensions:** Width: 64 mm  
Height: 155 mm  
Depth: 56 mm

**Miniature circuit-breaker/fuse:** 4 A

**Packs of:** 1 pc(s).

**Weight/pack:** 0.38 kg

<b>EAN:</b>	4028177638631
<b>Customs tariff number:</b>	85162999
<b>ETIM 6.0:</b>	EC000737
<b>ETIM 5.0:</b>	EC000737
<b>eCl@ss 8.0/8.1:</b>	27180710
<b>eCl@ss 7.0/7.1:</b>	27180710
<b>eCl@ss 6.0/6.1:</b>	27180710
<b>eCl@ss 5.1/5.1.4:</b>	27180710
<b>Product description:</b>	SK enclosure heater, without fan, 23-30 W, 110-240 V, 1~, 50/60 Hz, WHD: 64 x 155 x 56 mm
<b>Approvals</b>	
<b>Approvals:</b>	Approval overview CSA UR + C-UR VDE
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity