

Rittal – The System.

Faster – better – everywhere.

Enclosure heaters without fan – SK 3105.350

Date : Mar 15, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Enclosure heaters without fan – SK 3105.350

created: 15.03.2017 build on www.rittal.com/uk-en



Product description

Supply includes: PTC heater
Quick-connection terminal
Assembly parts

Note: For precise temperature control inside the enclosure, we recommend the enclosure internal thermostat or the digital enclosure internal temperature display and thermostat.
In order to prevent condensation on assemblies, a hygostat is recommended to regulate heating.
In larger enclosures, even heat distribution is best achieved by installing several low-output heaters.
The installation of heaters is generally advisable, in order to prevent condensation.

Note on Model No.: Special voltages available on request. We reserve the right to make technical modifications.

Product features

Continuous thermal output at 10°C: 63 W - 75 W

Rated operating voltage: 110 V - 240 V, 1~, 50 Hz/60 Hz

Dimensions: Width: 64 mm
Height: 230 mm
Depth: 56 mm

Pre-fuse: Miniature circuit-breaker/fuse: 4 A

Packs of: 1 pc(s).

Weight/pack: 0.6 kg

EAN:	4028177908390
Customs tariff number:	85162999
ETIM 6.0:	EC000737
ETIM 5.0:	EC000737
eCl@ss 8.0/8.1:	27180710
eCl@ss 7.0/7.1:	27180710
eCl@ss 6.0/6.1:	27180710
eCl@ss 5.1/5.1.4:	27180710

Approvals

Approvals:	Approval overview C-UR CSA UR UR + C-UR VDE
Certificates:	EAC
Declarations:	Declaration of conformity