Rittal - The System.

Faster – better – everywhere.

Enclosure heaters without fan – SK 3105.360

Date: Mar 15, 2017



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Enclosure heaters without fan - SK 3105.360

created: 15.03.2017 build on www.rittal.com/uk-en



Product description

Supply includes: PTC heater

Quick-connection terminal

Assembly parts

Note: For precise temperature control inside the enclosure, we recommend the enclosure internal

thermostat or the digital enclosure internal temperature display and thermostat.

In order to prevent condensation on assemblies, a hygrostat is recommended to regulate

heating.

In larger enclosures, even heat distribution is best achieved by installing several low-output

heaters.

The installation of heaters is generally advisable, in order to prevent condensation.

Product features	
Continuous thermal output at 10°C:	86 W - 100 W
Rated operating voltage:	110 V - 240 V, 1~, 50 Hz/60 Hz
Di	W: 44- 00

Dimensions: Width: 90 mm Height: 165 mm

Depth: 75 mm

Pre-fuse: Miniature circuit-breaker/fuse: 4 A

Packs of: 1 pc(s).

Weight/pack: 0.82 kg

EAN: 4028177865044

© Rittal 2017

Customs tariff number:	85162999
ETIM 6.0:	EC000737
ETIM 5.0:	EC000737
eCl@ss 8.0/8.1:	27180710
eCl@ss 7.0/7.1:	27180710
eCl@ss 6.0/6.1:	27180710
eCl@ss 5.1/5.1.4:	27180710
Approvals	
Approvals:	Approval overview C-UR CSA UR UR VDE
Certificates:	EAC
Declarations:	Declaration of conformity

2017 © Rittal Ltd UK

© Rittal 2017