Rittal - The System.

Faster – better – everywhere.

Enclosure heaters with fan – SK 3105.380

Date: Jan 17, 2017



Enclosure heaters with fan - SK 3105.380

created: 17.01.2017 build on www.rittal.com/uk-en



Product	descri	intion
FIOUUCI	uescii	puon

Supply includes: Quick-connection terminal

Assembly parts

Note: For precise temperature control inside the enclosure, we recommend the enclosure internal

thermostat or the digital enclosure internal temperature display and thermostat.

In order to prevent condensation on assemblies, a hygrostat is recommended to regulate

heating.

In larger enclosures, even heat distribution is best achieved by installing several low-output

heaters.

The installation of heaters is generally advisable, in order to prevent condensation.

Prod	luct	featu	rae
FIUU	ιucι	ıtaıu	162

Continuous thermal output at 10°C:

250 W - 265 W

Note: Continuous thermal output with fan

Rated operating voltage:

230 V, 1~, 50 Hz/60 Hz

Dimensions: Width: 103 mm

Height: 200 mm Depth: 103 mm

Pre-fuse: Miniature circuit-breaker/fuse: 4 A

Fans pre-integrated: yes

Packs of: 1 pc(s).

Weight/pack: 1.22 kg

© Rittal 2017

EAN:	4028177662865
Customs tariff number:	85162999
ETIM 6.0:	EC000737
ETIM 5.0:	EC000737
eCl@ss 8.0/8.1:	27180710
eCl@ss 7.0/7.1:	27180710
e CI@ss 6.0/6.1:	27180710
eCl@ss 5.1/5.1.4:	27180710
Approvals	
Approvals:	Approval overview CSA UR UR + C-UR VDE
Declarations:	Declaration of conformity

2017 © Rittal Ltd UK

© Rittal 2017