

Rittal – The System.

Faster – better – everywhere.

Roof-mounted fan, roof vent – SK 3140.140

Date : Jan 24, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Roof-mounted fan, roof vent – SK 3140.140

created: 24.01.2019 build on www.rittal.com/uk-en



Product description

Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 21 without filter mat IP 55 including filter mat
Protection category NEMA:	with standard filter: NEMA 12
Supply includes:	Complete unit ready to install, including filter mat
Note:	For energy-efficient operation of the fans, we recommend the use of thermostats or temperature displays

Product features

Air throughput (unimpeded air flow):	863 m ³ /h
Air throughput, unimpeded air flow (without filter mats):	863 m ³ /h / 942 m ³ /h
Air throughput, unimpeded air flow (with filter mats):	700 m ³ /h / 749 m ³ /h
Rated operating voltage:	400 V, 3~, 50 Hz/60 Hz 460 V, 3~, 60 Hz
Dimensions:	Width: 400 mm Height: 133 mm Depth: 400 mm

Required mounting cut-out:	Width: 258 mm Depth: 258 mm
Installation depth:	34.6 mm
Temperature range:	Bearing: -40°C...+70°C Operation (environment): -30°C...+55°C
Power consumption P_{sub-el-subcl}:	At 50 Hz: 90 W At 60 Hz: 122 W
Rated current (max.):	At 50 Hz: 0.17 A At 60 Hz: 0.19 A
Pre-fuse:	Motor circuit-breaker: 6,3 A...10 A
Diagonal fan:	Radial, rotary current motor
Packs of:	1 pc(s).
Weight/pack:	6 kg
EAN:	4028177709133
Customs tariff number:	84145915
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180707
Product description:	SK roof-mounted fan TopTherm, 863/942 m ³ /h, 400-460 V, 3~, 50/60 Hz, WHD: 400 x 133 x 400 mm
Approvals	
Approvals:	Approval overview CSA UL + C-UL - FTTA UR + C-UR
Certificates:	EAC

Declarations:Declaration of conformity
