

Rittal – The System.

Faster – better – everywhere.

► **Wall-mounted cooling units Blue e+ Total cooling output 1.60 kW – SK 3185.830**

Date : Jun 28, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted cooling units Blue e+ Total cooling output 1.60 kW – SK 3185.830

created: 28.06.2018 build on www.rittal.com/uk-en



Product description

Benefits: Average 75% energy savings thanks to speed-regulated components and heat pipe technology
Suitable for international use due to a unique multi-voltage capability
Longer service life of the components inside the enclosure and the cooling unit due to component-friendly cooling
Intuitive operation due to touch display and intelligent interfaces

Material: Sheet steel

Colour: RAL 7035

Protection category IP to IEC 60 529: Internal circuit IP 55

Supply includes: Assembly parts
Fully wired ready for connection (plug-in terminal strip)

Note: Please observe the mounting instructions.

Product features

Total cooling output to DIN EN 14511: L 35 L 35 at 50 Hz: 1.6 kW
L 35 L 35 at 60 Hz: 1.6 kW
L 35 L 50 at 50 Hz: 1.2 kW
L 35 L 50 at 60 Hz: 1.2 kW

Air throughput (unimpeded air flow): External circuit: 895 m³/h
Internal circuit: 700 m³/h

Rated operating 110 V - 240 V, 1~, 50 Hz/60 Hz

voltage:	380 V - 480 V, 3~, 50 Hz/60 Hz
Dimensions:	Width: 400 mm Height: 950 mm Depth: 310 mm
Temperature control:	e+ controller (factory setting +35°C)
Temperature range:	Bearing: -40°C...+70°C Operation (environment): -20°C...+60°C Setting range: +20°C...+50°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 750 g Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO ₂ e): 1.07 t
Power consumption P_{sub-el-subcl}:	L 35 L 35 at 50 Hz: 0.54 kW L 35 L 35 at 60 Hz: 0.54 kW L 35 L 50 at 50 Hz: 0.61 kW L 35 L 50 at 60 Hz: 0.61 kW
Rated output:	0.62 kW
Permissible operating pressure (p. max.):	24 bar
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	3.05
Seasonal energy efficiency ratio (SEER) 50/60 Hz L35 L35:	6.4
Packs of:	1 pc(s).
Weight/pack:	30.5 kg
EAN:	4028177708082
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704

eCl@ss 5.1/5.1.4: 27180704

Product description (long):	SK cooling unit Blue e+, wall-mounted, 1.6 kW, 110-240 V, 1~, 380-480 V, 3~, 50-60 Hz, Sheet steel, WHD: 400 x 950 x 310 mm
------------------------------------	---

Approvals

Approvals:	TÜV-Geprüfte Leistung TÜV-Geprüfte Sicherheit UL + C-UL - FTFA
-------------------	--

Declarations:	Declaration of conformity
----------------------	---------------------------
