

# Rittal – The System.

Faster – better – everywhere.

## **Wall-mounted cooling units Blue e+ Total cooling output 2.00 – 6.00 kW – SK 3189.640**

Date : Dec 18, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wall-mounted cooling units Blue e+ Total cooling output 2.00 – 6.00 kW – SK 3189.640

created: 18.12.2018 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Benefits:</b>	Average 75% energy savings thanks to speed-regulated components and heat pipe technology Suitable for international use due to a unique multi-voltage capability Longer service life of the components inside the enclosure and the cooling unit due to component-friendly cooling Intuitive operation due to touch display and intelligent interfaces
<b>Material:</b>	Stainless steel
<b>Colour:</b>	RAL 9007
<b>Protection category IP to IEC 60 529:</b>	Internal circuit IP 55
<b>Supply includes:</b>	Assembly parts Fully wired ready for connection (plug-in terminal strip)
<b>Note:</b>	Please observe the mounting instructions. Full installation not possible
<b>Options:</b>	For remote monitoring and networking of cooling units and chillers in the Blue e+ generation, please use the IoT interface (Model No. 3124.300). Increase machine availability and process reliability with remote monitoring of device data, statuses and system messages.

## Product features

<b>Variant:</b>	wall-mounted
<b>Total cooling output</b>	L 35 L 35 at 50 Hz: 5.8 kW

<b>to DIN EN 14511:</b>	L 35 L 35 at 60 Hz: 5.8 kW L 35 L 50 at 50 Hz: 4.2 kW L 35 L 50 at 60 Hz: 4.2 kW
<b>Air throughput (unimpeded air flow):</b>	External circuit: 2300 m³/h Internal circuit: 2300 m³/h
<b>Rated operating voltage:</b>	380 V - 480 V, 3~, 50 Hz/60 Hz
<b>Dimensions:</b>	Width: 450 mm Height: 1600 mm Depth: 393 mm
<b>Temperature control:</b>	e+ controller (factory setting +35 °C)
<b>Temperature range:</b>	Bearing: -40°C...+70°C Operation (environment): -20°C...+60°C Setting range: +20°C...+50°C
<b>Refrigerant/cooling medium:</b>	Refrigerant: R134a Quantity: 1750 g CO <sub>2</sub> equivalent (CO <sub>2</sub> e): 2.5 t
<b>Power consumption P<sub>sub-el-subcl</sub>:</b>	L 35 L 35 at 50 Hz: 2.2 kW L 35 L 35 at 60 Hz: 2.2 kW L 35 L 50 at 50 Hz: 2.2 kW L 35 L 50 at 60 Hz: 2.2 kW
<b>Rated power input:</b>	2.2 kW
<b>Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:</b>	2.64
<b>Seasonal energy efficiency ratio (SEER) 50/60 Hz:</b>	6.2
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	71.2 kg
<b>EAN:</b>	4028177934641
<b>Customs tariff number:</b>	84158200
<b>ETIM 6.0:</b>	EC000855
<b>ETIM 5.0:</b>	EC000855
<b>eCl@ss 8.0/8.1:</b>	27180704

<b>eCl@ss 7.0/7.1:</b>	27180704
<b>eCl@ss 6.0/6.1:</b>	27180704
<b>eCl@ss 5.1/5.1.4:</b>	27180704
<b>Approvals</b>	
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity