

Rittal – The System.

Faster – better – everywhere.

► TopTherm fan-and-filter units EMC – SK 3239.600

Date : Mar 14, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units EMC – SK 3239.600

created: 14.03.2017 build on www.rittal.com/uk-en



Product description

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 54
NEMA 12
With hose-proof hood: IP 56
With hose-proof hood: NEMA 3
With hose-proof hood: NEMA 3R
With hose-proof hood: NEMA 4
With hose-proof hood: NEMA 4X
With fine filter mat or hose-proof hood: IP 55
With fine filter mat or hose-proof hood: NEMA 12

Supply includes: Complete unit ready to install, including filter mat

Note: For energy-efficient operation of the fan-and-filter units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat

Product features

**Air throughput
(unimpeded air flow):** At 50 Hz: 105 m³/h
At 60 Hz: 120 m³/h

**Air throughput with
outlet filter including
standard filter mat:** Number of outlet filters: 1
Number of outlet filters: 2
Number of outlet filters: 1
Model No. of outlet filter: SK 3239.200
Model No. of outlet filter: SK 3239.200
Model No. of outlet filter: SK 3240.200
At 50 Hz: 87 m³/h
At 50 Hz: 93 m³/h
At 50 Hz: 98 m³/h
At 60 Hz: 100 m³/h

At 60 Hz: 108 m³/h
At 60 Hz: 111 m³/h

Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 204 mm Height: 204 mm
Required mounting cut-out:	Width: 177 mm Height: 177 mm
Build depth:	24 mm
Installation depth:	90 mm
Temperature range:	Bearing: -30°C...+70°C Operation (environment): -10°C...+55°C
EMC version:	yes
Power consumption Pel:	At 50 Hz: 19 W At 60 Hz: 18 W
Rated current (max.):	At 50 Hz: 0.12 A At 60 Hz: 0.11 A
Pre-fuse:	Miniature circuit-breaker/fuse: 2 A
Noise level:	At 50 Hz: 46 dB(A) At 60 Hz: 49 dB(A)
Diagonal fan:	Diagonal, self-starting shaded pole motor
Packs of:	1 pc(s).
Weight/pack:	1.2 kg
EAN:	4028177652446
Customs tariff number:	84145100
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716

eCl@ss 6.0/6.1:	27180716
------------------------	----------

eCl@ss 5.1/5.1.4:	27180705
--------------------------	----------

Approvals

Approvals:	Approval overview C-UR CSA UR UR + C-UR
-------------------	---

Certificates:	EAC
----------------------	-----

Declarations:	Declaration of conformity
----------------------	---------------------------
