

Rittal – The System.

Faster – better – everywhere.

► TopTherm fan-and-filter units – SK 3240.124

Date : Jan 17, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units – SK 3240.124

created: 17.01.2017 build on www.rittal.com/uk-en



Product description

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 54
NEMA 12
With hose-proof hood: IP 56
With hose-proof hood: NEMA 3
With hose-proof hood: NEMA 3R
With hose-proof hood: NEMA 4
With hose-proof hood: NEMA 4X
With fine filter mat or hose-proof hood: IP 55
With fine filter mat or hose-proof hood: NEMA 12

Supply includes: Complete unit ready to install, including filter mat

Product features

**Air throughput
(unimpeded air flow):** With DC: 180 m³/h

**Air throughput with
outlet filter including
standard filter mat:** Number of outlet filters: 1
Number of outlet filters: 2
Number of outlet filters: 1
Model No. of outlet filter: SK 3240.200
Model No. of outlet filter: SK 3240.200
Model No. of outlet filter: SK 3243.200
With DC: 138 m³/h
With DC: 165 m³/h
With DC: 165 m³/h

**Rated operating
voltage:** 24 V (DC)

Dimensions: Width: 255 mm

Height: 255 mm

Required mounting cut-out:	Width: 224 mm Height: 224 mm
Build depth:	25 mm
Installation depth:	107 mm
Temperature range:	Bearing: -30°C...+70°C Operation (environment): -30°C...+55°C
Power consumption Pel:	With DC: 10 W
Rated current (max.):	With DC: 0.43 A
Pre-fuse:	Miniature circuit-breaker/fuse: 2 A
Noise level:	With DC: 51 dB(A)
Diagonal fan:	Diagonal, DC motor
Packs of:	1 pc(s).
Weight/pack:	1.88 kg
EAN:	4028177651968
Customs tariff number:	84145100
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705

Approvals

Approvals: Approval overview
C-UR
CSA
UR

UR + C-UR

Declarations:

Declaration of conformity

2017 © Rittal Ltd UK