

# Rittal – The System.

Faster – better – everywhere.

► **TopTherm wall-mounted cooling units Total cooling output 0.30 kW – SK 3302.200**

Date : Apr 25, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TopTherm wall-mounted cooling units Total cooling output 0.30 kW – SK 3302.200

created : 25.04.2016 build on www.rittal.com/uk-en



## Product description

**Material:** Stainless steel

**Protection category  
IP to IEC 60 529:** External circuit IP 34  
Internal circuit IP 54

**Supply includes:** Nano-coated condenser  
Fully wired ready for connection (plug-in terminal strip)  
Drilling template  
Assembly parts

**Note on Model No.:** Extended delivery times.

**Packs of:** 1 pc(s).

**EAN:** 4028177379602

**Customs tariff  
number:** 84158200

**eCl@ss 5.1:** 27180704




**eCl@ss 7.0:** 27180704

**ETIM 6.0:** EC000855

## Product features

<b>Total cooling output to DIN EN 14511:</b>	L 35 L 35 at 50 Hz: 0.36 kW L 35 L 35 at 60 Hz: 0.38 kW L 35 L 50 at 50 Hz: 0.21 kW L 35 L 50 at 60 Hz: 0.23 kW
<b>Air throughput (unimpeded air flow):</b>	External circuit: 310 m <sup>3</sup> /h Internal circuit: 345 m <sup>3</sup> /h
<b>Rated operating voltage:</b>	230 V, 1~, 50 Hz/60 Hz
<b>Dimensions:</b>	Width: 280 mm Height: 550 mm Depth: 140 mm
<b>Temperature control:</b>	Basic controller (factory setting +35°C)
<b>Temperature range:</b>	Operation (environment): +10°C...+55°C Setting range: +30°C...+55°C
<b>Refrigerant/cooling medium:</b>	Refrigerant: R134a Quantity: 100 g
<b>Power consumption Pel:</b>	L 35 L 35 at 50 Hz: 0.28 kW L 35 L 35 at 60 Hz: 0.29 kW L 35 L 50 at 50 Hz: 0.29 kW L 35 L 50 at 60 Hz: 0.31 kW
<b>Rated current (max.):</b>	At 50 Hz: 1.6 A At 60 Hz: 1.7 A
<b>Start-up current max.:</b>	At 50 Hz: 3 A At 60 Hz: 3.4 A
<b>Pre-fuse:</b>	Miniature circuit-breaker/fuse: 10 A
<b>Permissible operating pressure (p. max.):</b>	25 bar
<b>Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:</b>	1.3
<b>Weight/pack:</b>	13 kg





## Approvals

**Approvals:**  CSA 1  
EN  
 TÜV-Geprüfte Sicherheit (EN, DE)  
 UR + C-UR (EN)


**Declarations:**  Declaration of conformity (EN, DE)

## Downloads


### Data sheets:

-  [Performance diagrams](#)  
EN
-  [Safety data sheet](#)  
EN
-  [Technical details](#)  
EN
-  [Technical system catalogue \(DE\)](#)

### Documentation:

-  [Instructions](#)  
EN

### Specialist literature:

-  [The Rittal technology library](#)  
EN

### CAD drawings:

Request