

Rittal – The System.

Faster – better – everywhere.

► **TopTherm wall-mounted cooling units, horizontal format Total cooling output 0.30 kW – SK 3302.310**

Date : Jan 13, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm wall-mounted cooling units, horizontal format Total cooling output 0.30 kW – SK 3302.310

created: 13.01.2017 build on www.rittal.com/uk-en



Product description

Material:	Sheet steel
Colour:	RAL 7035
Protection category IP to IEC 60 529:	External circuit IP 34 Internal circuit IP 54
Supply includes:	Nano-coated condenser Fully wired ready for connection (plug-in terminal strip) Drilling template Assembly parts

Product features

Total cooling output to DIN EN 14511:	L 35 L 35 at 60 Hz: 0.38 kW L 35 L 50 at 60 Hz: 0.23 kW
Air throughput (unimpeded air flow):	External circuit: 300 m ³ /h Internal circuit: 300 m ³ /h
Rated operating voltage:	115 V, 1~, 60 Hz
Dimensions:	Width: 525 mm Height: 340 mm Depth: 153 mm
Temperature control:	Basic controller (factory setting +35°C)

Temperature range:	Operation (environment): +10°C...+55°C Setting range: +30°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 95 g
Power consumption Pel:	L 35 L 35 at 60 Hz: 0.32 kW L 35 L 50 at 60 Hz: 0.37 kW
Rated current (max.):	At 60 Hz: 4 A
Start-up current max.:	At 60 Hz: 12 A
Pre-fuse:	Miniature circuit-breaker/fuse: / 10 A
Permissible operating pressure (p. max.):	25 bar
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	1.18
Packs of:	1 pc(s).
Weight/pack:	13 kg
EAN:	4028177429802
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704
eCl@ss 5.1/5.1.4:	27180704
Approvals	
Approvals:	TÜV-Geprüfte Sicherheit UR + C-UR
Declarations:	Declaration of conformity

