

Rittal – The System.

Faster – better – everywhere.

► Wall-mounted cooling units TopTherm "Blue e" Total cooling output 0.50 – 0.75 kW – SK 3303.500

Date : Apr 25, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted cooling units TopTherm "Blue e" Total cooling output 0.50 – 0.75 kW – SK 3303.500

created : 25.04.2016 build on www.rittal.com/uk-en



Product description

Material: Sheet steel

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** External circuit IP 34
Internal circuit IP 54

Supply includes: Nano-coated condenser
Fully wired ready for connection (plug-in terminal strip)
Drilling template
Assembly parts

Packs of: 1 pc(s).

EAN: 4028177322844

**Customs tariff
number:** 84158200

eCl@ss 5.1: 27180704






eCl@ss 7.0: 27180704

ETIM 6.0: EC000855

Product features





Total cooling output to DIN EN 14511:	L 35 L 35 at 50 Hz: 0.55 kW L 35 L 35 at 60 Hz: 0.66 kW L 35 L 50 at 50 Hz: 0.33 kW L 35 L 50 at 60 Hz: 0.4 kW
Air throughput (unimpeded air flow):	External circuit: 315 m ³ /h Internal circuit: 265 m ³ /h
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 280 mm Height: 550 mm Depth: 210 mm
Temperature control:	e-Comfort controller (factory setting +35°C)
Temperature range:	Operation (environment): +10°C...+55°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 170 g
Power consumption Pel:	L 35 L 35 at 50 Hz: 0.39 kW L 35 L 35 at 60 Hz: 0.41 kW L 35 L 50 at 50 Hz: 0.45 kW L 35 L 50 at 60 Hz: 0.42 kW
Rated current (max.):	At 50 Hz: 2.6 A At 60 Hz: 2.6 A
Start-up current max.:	At 50 Hz: 5.1 A At 60 Hz: 6.4 A
Pre-fuse:	Miniature circuit-breaker/fuse: 10 A
Permissible operating pressure (p. max.):	28 bar
Energy efficiency ratio (EER) 50 Hz L35 L35 to DIN EN 14511:	1.4
Weight/pack:	17 kg

Approvals


Approvals:	 <u>CSA</u> 1 EN  TÜV-Geprüfte Leistung (EN, DE)  TÜV-Geprüfte Sicherheit (EN, DE)  UR + C-UR (EN)
Declarations:	 <u>Declaration of conformity (EN, DE)</u>

Downloads


Data sheets:

-  [Performance diagrams](#)
EN
-  [Safety data sheet](#)
EN
-  [Technical details](#)
EN
-  [Technical system catalogue \(DE\)](#)

Documentation:

-  [Instructions](#)
EN

Specialist literature:

-  [The Rittal technology library](#)
EN

CAD drawings:

Request