

Rittal – The System.

Faster – better – everywhere.

► **TopTherm wall-mounted cooling unit
Blue e Total cooling
output 0.50 – 0.75 kW
– SK 3303.600**

Date : Jan 24, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm wall-mounted cooling unit Blue e Total cooling output 0.50 – 0.75 kW – SK 3303.600

created: 24.01.2019 build on www.rittal.com/uk-en



Product description

Material: Stainless steel

**Protection category
IP to IEC 60 529:** External circuit IP 34
Internal circuit IP 54

Supply includes: Nano-coated condenser
Fully wired ready for connection (plug-in terminal strip)
Drilling template
Assembly parts

Note: The technical specifications for the wall-mounted cooling unit 3361.540 apply with an external transformer connected.

Note on Model No.: Extended delivery times.

Product features

Variant: wall-mounted

**Total cooling output
to DIN EN 14511:** L 35 L 35 at 50 Hz: 0.55 kW
L 35 L 35 at 60 Hz: 0.66 kW
L 35 L 50 at 50 Hz: 0.33 kW
L 35 L 50 at 60 Hz: 0.4 kW

**Air throughput
(unimpeded air flow):** External circuit: 315 m³/h
Internal circuit: 265 m³/h

**Rated operating
voltage:** 230 V, 1~, 50 Hz/60 Hz

| | |
|--|---|
| Dimensions: | Width: 280 mm Height: 550 mm Depth: 210 mm |
| Temperature control: | e-Comfort controller (factory setting +35 °C) |
| Temperature range: | Operation (environment): +10°C...+55°C Setting range: +20°C...+55°C |
| Refrigerant/cooling medium: | Refrigerant: R134a Quantity: 170 g Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO ₂ e): 0.24 t |
| Power consumption P_{sub-el-subcl}: | L 35 L 35 at 50 Hz: 0.39 kW L 35 L 35 at 60 Hz: 0.41 kW L 35 L 50 at 50 Hz: 0.45 kW L 35 L 50 at 60 Hz: 0.42 kW |
| Rated current (max.): | At 50 Hz: 2.6 A At 60 Hz: 2.6 A |
| Start-up current max.: | At 50 Hz: 5.1 A At 60 Hz: 6.4 A |
| Miniature circuit-breaker/fuse: | 10 A |
| Permissible operating pressure (p. max.): | 28 bar |
| Packs of: | 1 pc(s). |
| Weight/pack: | 17 kg |
| EAN: | 4028177379640 |
| Customs tariff number: | 84158200 |
| ETIM 6.0: | EC000855 |
| ETIM 5.0: | EC000855 |
| eCl@ss 8.0/8.1: | 27180704 |
| eCl@ss 7.0/7.1: | 27180704 |
| eCl@ss 6.0/6.1: | 27180704 |
| eCl@ss 5.1/5.1.4: | 27180704 |

Product description: SK cooling unit Blue e, wall-mounted, 0.55 kW, 230 V, 1~, 50/60 Hz, Stainless steel, WHD: 280 x 550 x 210 mm

Approvals

| | |
|-------------------|---|
| Approvals: | CSA TÜV-tested safety UL + C-UL - FTFA UR + C-UR |
|-------------------|---|

| | |
|----------------------|-----|
| Certificates: | EAC |
|----------------------|-----|

| | |
|----------------------|---|
| Declarations: | Declaration of conformity Declaration of conformity - F-gas regulation |
|----------------------|---|