

Rittal – The System.

Faster – better – everywhere.

► Rack-mounted fans for 482.6 mm (19") Air throughput 320/480 m³/h – SK 3340.230

Date : Jan 13, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Rack-mounted fans for 482.6 mm (19") Air throughput 320/480 m³/h – SK 3340.230

created: 13.01.2017 build on www.rittal.com/uk-en



Product description

Supply includes: Fully wired unit ready for connection
Terminal strip and assembly parts

Product features

Air throughput (unimpeded air flow): 320 m³/h

Rated operating voltage: 230 V, 1~, 50 Hz/60 Hz

Dimensions: Width: 482.6 mm
Height: 44 mm
Depth: 200 mm

Distance between axes of fans: 85 mm

Temperature range: Operation (environment): -10°C...+55°C

Rated current (max.): At 50 Hz: 0.24 A
At 60 Hz: 0.22 A

Pre-fuse: Miniature circuit-breaker/fuse: 6 A

Noise level: At 50 Hz: 51 dB(A)

Number of fans: 2

Packs of:	1 pc(s).
Weight/pack:	2.24 kg
EAN:	4028177041448
Customs tariff number:	84145100
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705

Approvals

Approvals: Approval overview
UR + C-UR

Declarations: Declaration of conformity