

Rittal – The System.

Faster – better – everywhere.

► **TopTherm Blue e
roof-mounted cooling
unit Total cooling
output 0.50 - 4.00 kW
– SK 3359.510**

Date : Feb 21, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm Blue e roof-mounted cooling unit Total cooling output 0.50 - 4.00 kW – SK 3359.510

created: 21.02.2019 build on www.rittal.com/uk-en



Product description

Material: Sheet steel

Colour: RAL 7035

Protection category IP to IEC 60 529: External circuit IP 34
Internal circuit IP 54

Supply includes: Nano-coated condenser
Integral electric condensate evaporation
Fully wired ready for connection (plug-in terminal strip)
Drilling template
Assembly parts

Note: The roof-mounted cooling unit 3273.500 is also suitable for office applications, thanks to its low noise level.

Product features

Total cooling output to DIN EN 14511: L 35 L 35 at 50 Hz: 0.77 kW
L 35 L 35 at 60 Hz: 0.79 kW
L 35 L 50 at 50 Hz: 0.52 kW
L 35 L 50 at 60 Hz: 0.47 kW

Air throughput (unimpeded air flow): External circuit: 910 m³/h
Internal circuit: 440 m³/h

Rated operating voltage: 115 V, 1~, 50 Hz/60 Hz

Dimensions: Width: 597 mm

Height: 417 mm
Depth: 380 mm

Temperature control:	e-Comfort controller (factory setting +35 °C)
Temperature range:	Operation (environment): +10°C...+55°C Setting range: +20°C...+55°C
Refrigerant/cooling medium:	Refrigerant: R134a Quantity: 400 g Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO _{2e}): 0.57 t
Type of electrical connection:	Plug-in terminal strip
Duty cycle:	100 %
Power consumption P_{sub-el-subcl}:	L 35 L 35 at 50 Hz: 0.33 kW L 35 L 35 at 60 Hz: 0.43 kW L 35 L 50 at 50 Hz: 0.49 kW L 35 L 50 at 60 Hz: 0.42 kW
Rated current (max.):	At 50 Hz: 5.6 A At 60 Hz: 7.4 A
Start-up current max.:	At 50 Hz: 18.4 A At 60 Hz: 18 A
Pre-fuse:	Transformer circuit-breaker: 11 A...16 A
Permissible operating pressure (p. max.):	28 bar
Packs of:	1 pc(s).
Weight/pack:	37 kg
EAN:	4028177429628
Customs tariff number:	84158200
ETIM 6.0:	EC000855
ETIM 5.0:	EC000855
eCl@ss 8.0/8.1:	27180704
eCl@ss 7.0/7.1:	27180704
eCl@ss 6.0/6.1:	27180704

eCl@ss 5.1/5.1.4:	27180704
Product description:	SK cooling unit Blue e, roof-mounted, 0.77 kW, 115 V, 1~, 50/60 Hz, Sheet steel, WHD: 597 x 417 x 380 mm
Approvals	
Approvals:	TÜV-tested safety UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity Declaration of conformity - F-gas regulation