

Rittal – The System.

Faster – better – everywhere.

► Air/water heat exchangers Wall-mounted – SK 3373.100

Date : Jan 13, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Air/water heat exchangers Wall-mounted – SK 3373.100

created: 13.01.2017 build on www.rittal.com/uk-en



Product description

Design:	Water-carrying parts, copper/brass (Cu/CuZn)
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Supply includes:	Fully wired ready for connection (plug-in terminal strip) Drilling template Sealing and assembly parts
Note:	Integral non-return valve for version with e-Comfort controller

Product features

Total cooling output:	L 35 W 10 at 400 l/h: 2 kW
Air throughput (unimpeded air flow):	Internal circuit at 50 Hz: 880 m ³ /h Internal circuit at 60 Hz: 950 m ³ /h
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 400 mm Height: 950 mm Depth: 145 mm
Temperature control:	Basic controller (factory setting +35°C)
Temperature range:	Operation (environment): +1°C...+70°C

Setting range: +20°C...+55°C
Water inlet: +1°C...+30°C

Refrigerant/cooling medium:	Cooling medium: Water (see Internet for specifications)
Duty cycle:	100 %
Power consumption Pel:	At 50 Hz: 110 W At 60 Hz: 140 W
Rated current (max.):	At 50 Hz: 0.49 A At 60 Hz: 0.61 A
Pre-fuse:	Miniature circuit-breaker/fuse: 4 A
Permissible operating pressure (p. max.):	1 bar - 10 bar
Water connections:	½" connector sleeve G ¾" external thread
Packs of:	1 pc(s).
Weight/pack:	20 kg
EAN:	4028177495678
Customs tariff number:	84158300
ETIM 6.0:	EC002515
ETIM 5.0:	EC002515
eCl@ss 8.0/8.1:	27180712
eCl@ss 7.0/7.1:	27180712
eCl@ss 6.0/6.1:	27180712
eCl@ss 5.1/5.1.4:	27180712

Approvals

Approvals:	Approval overview C-UR CSA UR + C-UR
Declarations:	Declaration of conformity

