Rittal - The System.


Faster – better – everywhere.

Conductor connection clamps – SV 3454.500



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

Conductor connection clamps – SV 3454.500 created: 24.01.2019 build on www.rittal.com/uk-en



Product description	
Description:	For connecting round conductors and laminated copper bars.
Material:	Sheet steel
Surface finish:	Zinc-plated, passivated
Note:	Wire end ferrules should be used with fine wire conductors.
Product features	
To fit busbars:	Cross-section (thickness): 5 mm
Clamping area for laminated copper bars:	Width: 22.5 mm Height: 20 mm
Connection for round conductor cross-sections:	70 mm² - 185 mm²
Packs of:	15 pc(s).
Weight/pack:	2 kg
EAN:	4028177042711
Customs tariff number:	85369010
ETIM 6.0:	EC000001

© Rittal 2019

ETIM 5.0:	EC000001
eCl@ss 8.0/8.1:	27141146
eCl@ss 7.0/7.1:	27141146
eCl@ss 6.0/6.1:	27141146
eCl@ss 5.1/5.1.4:	27370302
Product description:	SV Conductor connection clamp, 70-185 mm², clamping area WH: 22,5x20 mm, for bar thickness 5 mm
Approvals	
Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity

© Rittal 2019