Rittal – The System.

Faster – better – everywhere.

Conductor connection clamp - SV 3459.500




ENCLOSURES

POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Conductor connection clamp – SV 3459.500 created: 24.10.2019 build on www.rittal.com/uk-en



Product description	
Description:	For connecting round conductors and laminated copper bars.
Material:	Sheet steel
Surface finish:	Zinc-plated, passivated
Note:	Wire end ferrules should be used with fine wire conductors
Product features	
To fit busbars:	Cross-section (thickness): 10 mm
Clamping area for laminated copper bars:	Width: 22.5 mm Height: 20 mm
Connection for round conductor cross- sections:	70 mm² - 185 mm²
Packs of:	15 pc(s).
Weight/pack:	2.04 kg
Copper weight (kg per piece):	0
EAN:	4028177042780
Customs tariff number:	85369010

ETIM 6.0:	EC00001
eCl@ss 8.0/8.1:	27141146
eCl@ss 6.0/6.1:	27141146
Product description:	SV Conductor connection clamp, 70-185 mm ² , clamping area WH: 22,5x20 mm, for bar thickness 10 mm
Approvals	
Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity