

# Rittal – The System.

Faster – better – everywhere.

## Door-operated switch – SZ 4127.210

Date : Jan 25, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Door-operated switch – SZ 4127.210

created: 25.01.2019 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

**Function principle:** The toggle is actuated via the tubular door frame of the sheet steel door, or in the case of glazed doors, via an adaptor included with the supply.

## Product features

**Rated operating voltage:** 400 V

**Installation options:** for TS enclosures with installed large swing frame  
for standard and courtesy light

**For rated current (max.):** 240 V AC, 6 A

**Rated insulation voltage:** 400 V AC

**Rated impulse withstand voltage, phase to phase:** 6000 V AC

**Packs of:** 1 pc(s).

**Weight/pack:** 0.26 kg

**EAN:** 4028177581326

**Customs tariff number:** 85369095

**ETIM 6.0:** EC002626

**ETIM 5.0:** EC002626

<b>eCl@ss 8.0/8.1:</b>	27189266
<b>eCl@ss 7.0/7.1:</b>	27119116
<b>eCl@ss 6.0/6.1:</b>	27119116
<b>eCl@ss 5.1/5.1.4:</b>	27189241
<b>Product description:</b>	SZ Door-operated switch, with toggle, without connection cable, UL
<b>Approvals</b>	
<b>Approvals:</b>	CCC CSA
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity