

Rittal – The System.

Faster – better – everywhere.

Energy-box, 482.6 mm (19") – DK 7480.035

Date : Oct 22, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Energy-box, 482.6 mm (19") – DK 7480.035

created: 22.10.2019 build on www.rittal.com/uk-en



Product description

Description: Depth-variable top hat rail for installed equipment to DIN 43 880 in sizes 1 – 3, e.g. to accommodate flush-type socket outlets, circuit-breakers, etc., with cable clamping at the rear and one N and one PE rail each on an insulated base/plinth.

Colour: RAL 7035

Supply includes: Energy-Box with depth-variable top hat rail for installed equipment to DIN 43880, sizes 1 – 3, with brush strip for cable entry at the rear
Plastic hood including extension cover (UL94-V0)
4 connection clamps, 35 mm²
18 connection clamps, 16 mm²
2 blanking covers
12 clips for strain relief of the connection cables
Identification strips, self-adhesive

Note: Individual population with circuit-breakers at the factory available on request.

Product features

Dimensions: Width: 482.6 mm
Width: 19"
Height: 132.5 mm
Depth: 155 mm

Units: 3 U

Max. pitch units @ 18 mm: 22

Packs of: 1 pc(s).

Weight/pack: 2.55 kg

Copper weight (kg per piece):	0
EAN:	4028177166004
Customs tariff number:	94032080
ETIM 6.0:	EC002620
eCl@ss 8.0/8.1:	27189261
eCl@ss 6.0/6.1:	27142604
Product description:	DK Energy-Box, WHD: 482,6 (19")x132,5x155 mm, max. 22 pitch units
Approvals	
Certificates:	EAC
Declarations:	Declaration of conformity