







Spring-Clamp Connection Terminal Blocks

Internal Component Blocks

	1492-LD4DF			1492-LD4DR			1492-LD4SS*		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Two-level terminal block with an IN4007 diode in forward bias between the 2 levels.			Two-level terminal block with an IN4007 diode in reverse bias between the 2 levels.			Two level terminal block with an MOV between the 2 levels.		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC		500V AC/DC	600V AC/DC		500V AC/DC	600V AC/DC	600V AC/DC	140V AC/DC
Maximum Current	25 A	30 A	32 A	25 A	30 A	32 A	120V	—	
Component Current/Wattage Rating*	1 A			1 A			25 A	30 A	32 A
Wire Range (Rated Cross Section)	#26...10 AWG		4 mm ²	#26...10 AWG		4mm ²	#26...10 AWG	26...10 AWG	4mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.39 in. (10 mm)		
Density	49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)			49 pcs/ft (163 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Color	Black	1492-LD4DF	1	1492-LD4DR	1	1492-LD4SS	1		
Accessories	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.
Mounting Rails 1 m Symmetrical DIN (Steel)	199-DR1		10	199-DR1		10	199-DR1		10
1 m Symmetrical DIN (Aluminum)	1492-DR5		10	1492-DR5		10	1492-DR5		10
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6		2	1492-DR6		2	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2	1492-DR7		2	1492-DR7		2
End Barrier	Grey	1492-EBLD4	20	1492-EBLD4	20	1492-EBLD4	20		
End Anchors and Retainers Screwless End Retainer	1492-ERL35		20	1492-ERL35		20	1492-ERL35		20
DIN Rail – Normal Duty	1492-EAJ35		100	1492-EAJ35		100	1492-EAJ35		100
DIN Rail – Heavy Duty	1492-EAHJ35		50	1492-EAHJ35		50	1492-EAHJ35		50
Jumpers Plug-in Center Jumper – 10-pole	1492-CJK6-10		20	1492-CJK6-10		20	1492-CJK6-10		20
Plug-in Center Jumper – 9-pole	1492-CJK6-9		20	1492-CJK6-9		20	1492-CJK6-9		20
Plug-in Center Jumper – 8-pole	1492-CJK6-8		20	1492-CJK6-8		20	1492-CJK6-8		20
Plug-in Center Jumper – 7-pole	1492-CJK6-7		20	1492-CJK6-7		20	1492-CJK6-7		20
Plug-in Center Jumper – 6-pole	1492-CJK6-6		20	1492-CJK6-6		20	1492-CJK6-6		20
Plug-in Center Jumper – 5-pole	1492-CJK6-5		20	1492-CJK6-5		20	1492-CJK6-5		20
Plug-in Center Jumper – 4-pole	1492-CJK6-4		60	1492-CJK6-4		60	1492-CJK6-4		60
Plug-in Center Jumper – 3-pole	1492-CJK6-3		60	1492-CJK6-3		60	1492-CJK6-3		60
Plug-in Center Jumper – 2-pole	1492-CJK6-2		60	1492-CJK6-2		60	1492-CJK6-2		60
Other Accessories Test Plug	1492-TP23		20	1492-TP23		20	1492-TP23		20
Marking Systems Snap-In Marker Cards	1492-M6X10 (120/card)		5	1492-M6X10 (120/card)		5	1492-M6X10 (120/card)		5
Snap-In Marker Cards	1492-M6X5 (200/card)		5	1492-M6X5 (200/card)		5	1492-M6X5 (200/card)		5

* For component specifications, see Surge Suppressor Performance Characteristics and Electrical Component DataΔ