10

Guards

	Description	Туре	Cat. No.
Cat. No. 800T-N13		1 in. guard for non-illuminated	800T-N13
	Bul. 800T Push Button Guards Momentary push button guards to reduce the risk of accidental operation.	1/2 in. guard for non-illuminated	800T-N143
		1-1/2 in. guard for illuminated	800T-N93
		1-1/2 in. guard for non-illuminated with locking attachment	800T-N39
Cat. No. 800H-N152	Bul. 800H Illuminated Push Button Guard This guard provides additional protection against accidental operation of the push button unit. 1-1/2 in. (38.1 mm) guard for illumination units.		800H-N152
Cat. No. 800T-N226	Bul. 800T 18 mm Guard Provides side protection for 18 mm pilot lights.		800T-N226
	Bul. 800H Stainless Steel Guard Used on non-illuminated push buttons that have protective boots as shown on page 10-39.		800H-N153
Cat. No. 800H-N153			
	Bul. 800T Mushroom Push Button Guards Momentary mushroom guards for standard and jumbo mushroom push buttons. Reduces the risk of accidental operation.	Standard guard	800T-N129
		Standard guard with set screw Jumbo guard	800T-N165 800T-N151
Cat. No. 800T-N129		Jumbo guard with set screw	800T-N154
	Description	Type of Finish	Cat. No.
Pr Pr IIII un us	Bul. 800T/H Protective Guard Protective ring for Bul. 800T 2-position push-pull operators. Illuminated or non-illuminated. Often used to avoid unintentional tripping of E-stop operators. This guard is used with standard size button (40 mm dia.).	Stainless steel	800T-N310
Cat. Nos. 800T-N310 and 800T-NX1320	B:	Black	800T-NX132
and the second s	Description	Operator Size	Cat. No.
	Bul. 800T/H Jumbo Protective Guard Protective ring for Bul. 800T 2-position push-pull operators. Illuminated or non-illuminated. Often used to avoid unintentional tripping of E-stop operators.	60 mm (Jumbo)	800T-N310
Cat. No. 800T-N310J		63 mm	800T-N310L
Cat. No. 800T-N381	Bul. 800T/H Protective Guard Protective ring for Bul. 800T trigger action E-stop operators.	45 mm	800T-N381
		60/63 mm	800T-N381I
	Bul. 800T/H		
30	Ramp Guard For Bul. 800T/800H 2- and 3-position illuminated and non-ill size button only (40 mm dia.).	uminated push-pull units. Standard	800T-N339

