


Spring-Clamp Connection Terminal Blocks

Single-Circuit Automotive Fuse Block

1492-LAFB6

Dimensions are not intended to be used for manufacturing purposes.
Note: Height dimension is measured from top of rail to top of terminal block.



Specifications		Single-circuit automotive style fuse terminal block with or without LED blown fuse indication		
Certifications		UL	CSA	IEC
Voltage Rating	-LAFB6	300V AC/DC		250V AC/DC
	-LAFB624	10...36V AC/DC		
Maximum Current		30 A	25 A	30 A
Wire Range (Rated Cross Section)		#22...12 AWG	#22...10 AWG	0.5...6 mm ²
Wire Strip Length		0.394 in. (10 mm)		
Density		37 pcs/ft (123 pcs/m)		
Housing Temperature Range		-58...+248 °F (-50...+120 °C)		
Terminal Blocks		Cat. No.	Pkg Qty.	
Color	Black (without blown fuse indication)	1492-LAFB6	25	
	Black (with blown fuse indication)	1492-LAFB624	25	
Accessories		Cat. No.	Pkg Qty.	
Mounting Rails				
1 m Symmetrical DIN (Steel)		199-DR1	10	
1 m Symmetrical DIN (Aluminum)		1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2	
End Barrier	Black	1492-EBLAFB6	50	
End Anchors				
Screwless End Retainer		1492-ERL35	20	
DIN Rail - Normal Duty		1492-EAJ35	100	
Din Rail - Heavy Duty		1492-EAHJ35	50	
Jumpers				
Plug-in Center Jumper — 32-Pole		1492-CJL8-32	10	
Plug-in Center Jumper — 4-Pole		1492-CJL8-4	60	
Plug-in Center Jumper — 3-Pole		1492-CJL8-3	60	
Plug-in Center Jumper — 2-Pole		1492-CJL8-2	60	
Test Adapter		1492-TPL8	25	
Marking Systems				
Snap-in Marker Cards		1492-M5X8 (144/card)	5	
Snap-In Marker Cards		1492-M6X5 (200/card)	5	

