




IEC Terminal Covers

	Description†	Package Quantity	Field Modification Cat. No.
	IEC line or load terminal covers for 108 and 135 A devices. Dead front protection	1	150-TC1
	IEC line or load terminal covers for 201...251 A devices. Dead front protection	1	150-TC2
	IEC line or load terminal covers for 317...480 A devices. Dead front protection	1	150-TC3

† 5...85 A units have terminal guards standard. No additional terminal guards are required.

Human Interface and Communication Modules

	Description		Cat. No.	
	Hand-Held Human Interface Modules	LCD Display, Full Numeric Keypad*	20-HIM-A3	
		LCD Display, Programmer Only*	20-HIM-A5	
	Door-Mounted Human Interface Modules	Remote (Panel Mount) LCD Display, Full Numeric Keypad		20-HIM-C3S
		LCD Display, Programmer Only HIM (includes 3 m cable)		20-HIM-C5S
	Human Interface Module Interface Cables	PowerFlex HIM Interface Cable, 1 m (39 in)		20-HIM-H10
		Cable Kit (Male-Female) 0.33 m (1.1 ft)		1202-H03
		Cable Kit (Male-Female) 1 m (3.3 ft)		1202-H10
		Cable Kit (Male-Female) 3 m (9.8 ft)		1202-H30
		Cable Kit (Male-Female) 9 m (29.5 ft)		1202-H90
		DPI/SCANport™ One to Two Port Splitter Cable		1203-S03
Description (IP30/Type 1)		For Use With		
	Communication Modules	RS485 DF1 Communication Adapter	20-COMM-S	
		PROFIBUS™ DP Communication Adapter	20-COMM-P	
		ControlNet™ Communication Adapter (Coax)	20-COMM-C	
		Interbus™ Communication Adapter	20-COMM-I	
		Modbus/TCP Communication Adapter	20-COMM-M	
		DeviceNet™ Communication Adapter	20-COMM-D	
		EtherNet/IP™ Communication Adapter	20-COMM-E	
		HVAC Communication Adapter	20-COMM-H	
ControlNet™ Communication Adapter (Fiber)	20-COMM-Q			
	DriveTools™	Programming Software	WIN NT/2000/XP	
	DriveTools™ Sp	Programming Software	WIN NT/2000/XP	
	AnaCANda™ RS-232 to DPI	PC Interface	Serial	
	DPI to USB	PC Interface	USB	

* Requires a 20-HIM-H10 cable to connect to the SMC Flex.