

Panel Mount Signaling Devices

Overview/Product Selection



Bulletin 855P — Panel Mount Signaling Products

- Mounts in Standard 22.5 mm Hole
- Watertight Panel Alarms in 3 Different Sizes
- Sound Output Ranging from 80 dB @ 1 Meter to 105 dB @ 1 Meter
- IP65 Environmental Rating
- UL Type 4/4X/13
- Selectable Continuous or Pulsing Tone on 30 mm and 45 mm
- Selectable Continuous, Wobble or Pulsing Tone on 65 mm
- Combination Sounder and LED products
- Panel Mount Strobe or LED Indicator products
- Plug-in Terminal Blocks, IP2X Rated

Table of Contents

Product Selection this page
 Accessories..... 6
 Specifications..... 7
 Approximate Dimensions..... 8
Standards Compliance and Certifications
 EN 60947-5-1
 EN 61000-6-2
 EN 50081-2
 UL 508
 CSA 22.2 No. 14
 cULus Listed (File No. E14840, Guide No. NKCR)
 CE Marked

Product Selection

Bulletin 855P — Panel Mount Sounder

855P – $\frac{B}{a}$ $\frac{10}{b}$ $\frac{ME}{c}$ $\frac{22}{d}$



30 mm Panel Mount Sounder



45 mm Panel Mount Sounder



65 mm Panel Mount Sounder

a

Housing Color	
Code	Description
B	Black

b

Voltage	
Code	Description
30	12...24V AC/DC
10	120V AC
20	240V AC

c

Size	
Code	Description
SE	30 mm
ME	45 mm
LE	65 mm

d

Mounting Hole	
Code	Description
22	22.5 mm

Housing Color	Voltage	Size	Cat. No.
Black	12...24V AC/DC	30 mm	855P-B30SE22
		45 mm	855P-B30ME22
		65 mm	855P-B30LE22
	120V AC	30 mm	855P-B10SE22
		45 mm	855P-B10ME22
		65 mm	855P-B10LE22

