


Busbars

	Height x Width [mm (in.)]	Current Rating [A] ⁽¹⁾	UL Current Rating [A]	Length = 800 mm (31.5 in.)		Length = 1200 mm (47.24 in.)		Length = 2400 mm (94.5 in.)	
				Pkg. Qty.	Cat. No.	Pkg. Qty.	Cat. No.	Pkg. Qty.	Cat. No.
	12 x 5 (0.47 x 0.19)	200	150	3	141A-B125A	3	141A-B125C	12	141A-B125N
	15 x 5 (0.59 x 0.19)	250	—		141A-B155A		141A-B155C		141A-B155N
	20 x 5 (0.79 x 0.19)	320	362		141A-B205A		141A-B205C		141A-B205N
	25 x 5 (0.98 x 0.19)	400	—		141A-B255A		141A-B255C		141A-B255N
	30 x 5 (1.18 x 0.19)	450	500		141A-B305A		141A-B305C	141A-B305N	
	12 x 10 (0.47 x 0.38)	360	300		141A-B1210A		141A-B1210C	6	141A-B1210N
	20 x 10 (0.79 x 0.38)	520	564		141A-B2010A		141A-B2010C		141A-B2010N
	30 x 10 (1.18 x 0.38)	630	756		141A-B3010A		141A-B3010C		141A-B3010N

(1) Ratings shown are based on tested conditions at an ambient temperature of 35 °C (95 °F) and a busbar temperature of 65 °C (149 °F).