

## EU Declaration of Conformity

Product: IEC Miniature Circuit Breaker Accessories

Name and address of the manufacturer: Name and address of the authorised representative:

Rockwell Automation Inc.Rockwell Automation B.V.1201 South 2nd StreetRivium Promenade 160

Milwaukee, WI 53204 2909 LM Capelle aan den Ijssel

U.S.A. The Netherlands

This declaration of conformity is issued under the sole responsibility of the manufacturer.

Object of the declaration: Allen-Bradley 189 and 1489 Series

(reference the attached list of catalogue numbers)

The object of the declaration described above is in conformity with the relevant Union harmonisation legislation:

2014/35/EU Low Voltage Directive (LVD) 2011/65/EU RoHS Directive (RoHS)

References to the relevant harmonised standards used or references to the other technical specifications in relation to

which conformity is declared:

EN 60947-1:2007 + A1:2011 Low-voltage switchgear and controlgear – Part 1: General rules

EN 60947-5-1:2004 + A1:2009 Low-voltage switchgear and controlgear – Part 5-1: Control circuit devices

and switching elements – Electromechanical control circuit devices

EN 50581:2012 Technical documentation for the assessment of electrical and electronic

products with respect to the restriction of hazardous substances

Signed for and on behalf of the above named manufacturer:

Place and date of issue: Milwaukee, WI USA 27-June-2017

Name, function: Daniel L. Nachtigall, Technical Leader – Product Certification Engineering

Jain L. Nachtigall

Signature:



Catalogue number	Series 1	Description
189-AL11		Auxiliary contact, left side, 1 N.O./1 N.C.; 400V AC, 220V DC maximum
189-AL02		Auxiliary contact, left side, 2 N.C.; 400V AC, 220V DC maximum
189-AL20		Auxiliary contact, left side, 2 N.O.; 400V AC, 220V DC maximum
189-AB01		Auxiliary contact, bottom, 1 N.C.; 400V AC, 220V DC maximum
189-AB10		Auxiliary contact, bottom, 1 N.O.; 400V AC, 220V DC maximum
189-AR11		Auxiliary contact, right side, 1 N.O./1 N.C.; 400V AC, 220V DC maximum
189-AR02		Auxiliary contact, right side, 2 N.C.; 400V AC, 220V DC maximum
189-AR20		Auxiliary contact, right side, 2 N.O.; 400V AC, 220V DC maximum
189-ASCR3		Auxiliary/signal contact, right side, 1 C.O.; 400V AC, 220V DC maximum
189-AR3		Auxiliary contact, right side, 1 C.O.; 400V AC, 220V DC maximum
1489-AMRA3		Auxiliary contact, right side, 1 N.O./1 N.C. (1 C.O.); 400V AC, 220V DC maximum
1489-AMRS3		Signal contact, right side, 1 N.O./1 N.C. (1 C.O.); 400V AC, 220V DC maximum

<sup>1)</sup> If no series number is given, then all series are covered