VersaView 6300P Panel PC



Features and Benefits

- Available in display sizes from 12.1" to 24"
- Resolutions include FHD / HD / SVGA / SXGA / XGA / WXGA
- Available in both Standard or Low Profile bezels
- Standard Aluminum bezel units support various resolutions including high definition displays
- Features Low Profile units in standard definition and full high definition displays with the following bezel variants:
 - -Aluminum
 - -Aluminum Glass True Flat
- Analog resistive and projected capacitive (for multitouch operation)
- Four Ethernet 10/100/1000 Mbps ports
- Supports "Jumbo Frame" and "Wake on LAN" network standards
- Available with Microsoft Windows 10 IoT Enterprise 2019 LTSC
- Variations available with long distance support for up to two additional displays
- Mass storage types up to 1 TB that include mSATA, SSD SATA III, CFAST (up to 128 GB)
- Up to 32 GB of SODIMM DDR4 RAM
- USB variations of 1x USB 2.0 (Type A) front and rear and up to 3x USB 3.0 rear (Type-A)
- 1RS-232 (DB9M) serial port
- 1x DVI-D video output
- IP65 / IP66 (model dependent)
- Fanless construction
- Additional options in TPM, PCI Expansion Slots, additional communications
- 24V DC (18V to 32V DC) isolated power
- Operating temperature 0°C to +50°C
- CE, c-UL-us LISTED (61010), RCM approvals



6300P Low Profile Panel PC (Front)



6300P Low Profile Panel PC (Back)

VersaView® 6300 is a complete portfolio of open architecture industrial PCs, thin clients and monitors. This broad and adaptable line offers the flexibility you need to meet your specific performance requirements.

The VersaView 6300P Panel PC is based on the seventh generation Core i3, i5 and i7 of the Intel Kaby Lake H platform and Intel Celeron of the Skylake allowing it to handle complex industrial applications. Touch screen technologies, which enhance ease of use, include analog resistive and projected capacitive (for multitouch operation). This Panel PC is available in a variety of display sizes and resolutions. There are options of either Standard or Low Profile bezel units. Both have resolutions up to full high definition.

IP65 / IP66 (model dependent) environmental protection makes the VersaView 6300P Panel PC an excellent match for washdown applications such as food processing and life sciences. Fanless construction helps to ensure low maintenance operation and enhance longevity.

The VersaView 6300P Panel PC is capable of supporting Windows and Linux operating systems and contains up to 1TB of mass storage. It offers an "all in one" motherboard helping to provide reliability in shock and vibration prone environments. It includes four Ethernet ports and supports "Jumbo Frame" and "Wake on LAN" network standards making it easy to incorporate into your existing systems.

Plant floor environments are demanding. VersaView Panel PCs are a solid match for applications requiring a high performance Human Machine Interface (HMI). This product family integrates completely with our FactoryTalk® View SE and FactoryTalk View ME software for seamless assimilation within your facility. The portfolio has various design options available making this robust product family a great choice for plant floor environments.



VersaView 6300P Panel PC

	Standard Bezel Aluminum	Low Profile Bezel Aluminum and Aluminum Glass True Flat
LED backlight TFT LCD	12.1" - 1024x768 15.0" - 1024x768 17" - 1280x1024 19" - 1280x1024	12.1" W - 1280x800 15.6" W - 1920x1080 18.5" W - 1920x1080 21.5" W - 1920x1080 24" W - 1920x1080
Touch screen	Resistive 5 wires	P-CAP Multitouch Aluminum Glass True Flat Resistive 5 wires – Aluminum
Protection grade	IP65 / IP66 (model dependent)	
Processor (soldered)	Intel Celeron G3900E 2.40 GHz, 2 cores/2 threads, 2MB L2 cache, soldered Intel Core i3-7100E 2.9 GHz, 2 cores/4 threads, 3 MB smart cache, soldered Intel Core i7-7820EQ 3.0 GHz (3.7 GHz Turbo), 4 cores/8 threads, 8 MB smart cache	
Chipset	Intel HM170 PCH (Platform Controller Hub) Intel HM175 PCH (Platform Controller Hub) - Included into processor chip	
Video controller	Intel HD Graphics 510 integrated into Intel Celeron microprocessor, 950MHz Intel HD Graphics 630 integrated in i3-7100E, 350/950 MHz Clock Intel HD Graphics 630 integrated in i5-7440EQ / i7-7820EQ, 350 MHz/1 GHz Clock	
System memory - RAM	4 GB/8 GB/16 GB/32 GB (2 x SODIMM DDR4-2400 module)	
Mass storage	1 x bootable up to 128 GB CFast SATA III slot on board with external front access 1 x onboard connector for direct insertion of mSATA up to 1 TB SSD SATA III 1 x onboard connector for 2.5" SSD SATA III up to 1 TB	
LAN	4 x Ethernet 10/100/1000 Mbps (RJ45 - 3 x Intel I210, 1 x Intel I219-LM)	
USB	3 x USB 3.0 rear (Type-A) 2 x USB 2.0 rear (Type-A) 1 x USB 2.0 front (Type-A)	3 x USB 3.0 rear (Type-A) 2 x USB 2.0 rear (Type-A)
Serial	1×RS232 (DB9M)	
Video output	1× DVI-D	
Expansion slots	1 x PCle x4 (5 Gb/s)	
Power	24V DC (18 to 32V DC) isolated	
Certified operating system	Microsoft® Windows 10 IoT Enterprise 2019 64 bit	
Operating temperature	Operating temperature: 0°C +50°C with Celeron/Core i3 processor, 0°C +45°C with Core i7 processor	
Approvals	CE (EN 61326-1, EN 61010-1, EN 61010-2-201), cULus LISTED (UL61010), RCM	



rockwellautomation.com -

expanding human possibility[®]

AMERICAS: Rockwell Automation, 1201 South Second Street, Milwaukee, WI 53204-2496 USA, Tel: (1) 414.382.2000, Fax: (1) 414.382.4444 EUROPE/MIDDLE EAST/AFRICA: Rockwell Automation NV, Pegasus Park, De Kleetlaan 12a, 1831 Diegem, Belgium, Tel: (32) 2 663 0600, Fax: (32) 2 663 0640 ASIA PACIFIC: Rockwell Automation, Level 14, Core F, Cyberport 3, 100 Cyberport Road, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846

> Allen-Bradley, expanding human possibility, FactoryTalk, Rockwell Automation and VersaView are trademarks of Rockwell Automation, Inc. Microsoft is a trademark of Microsoft Corporation.

> > Trademarks not belonging to Rockwell Automation are property of their respective companies